

Hong Kong Offshore LNG Terminal Project

Water Quality Monitoring Report for First Year of Operation of the LNG Terminal – January to March 2024 PREPARED FOR









DATE 12 April 2024

PROJECT NO. 0505354
















DOCUMENT DETAILS

DOCUMENT TITLE	Hong Kong Offshore LNG Terminal Project
DOCUMENT SUBTITLE	Water Quality Monitoring Report for First Year of Operation of the LNG Terminal – January to March 2024
PROJECT NUMBER	0505354
Date	12 April 2024
Version	0
Author	BW
Client name	CAPCO, HK Electric, HKLTL

DOCUMENT HISTORY

		ERM APPRO	OVAL TO ISSUE	
REVISION	AUTHOR	REVIEWED BY	NAME	DATE
0	BW	RC	JN	12/4/2024

CLIENT: CAPCO, HK Electric, HKLTL
PROJECT NO: 0505354 DATE: 12 April 2024 VERSION: 0

SIGNATURE PAGE

Hong Kong Offshore LNG Terminal Project

Water Quality Monitoring Report for First Year of Operation of the LNG Terminal – January to March 2024

Dr Jasmine Ng

Managing Partner

ERM-Hong Kong, Limited
2507, 25/F One Harbourfront
18 Tak Fung Street
Hunghom
Kowloon

Hong Kong

© Copyright 2024 by The ERM International Group Limited and/or its affiliates ('ERM'). All Rights Reserved.

No part of this work may be reproduced or transmitted in any form or by any means, without prior written permission of ERM.

VERSION: 0

CLIENT: CAPCO, HK Electric, HKLTL
PROJECT NO: 0505354 DATE: 12 April 2024







Hong Kong Offshore LNG Terminal Environmental Certification Sheet FEP-01/558/2018/A, FEP-02/558/2018/A and FEP-03/558/2018/B

Reference Document/Plan

Document/Plan to be Certified/ Verified: Water Quality Monitoring Report for First Year of

Operation of the LNG Terminal - January to March 2024

Date of Report: 12 April 2024

Date prepared by ET: 12 April 2024

Date received by IEC: 12 April 2024

Reference EP Requirement

EP Condition: Condition No. 5.1 of FEP-01/558/2018/A, FEP-

02/558/2018/A & FEP-03/558/2018/B

The Permit Holder shall implement the EM&A programme in accordance with the procedures and requirements as set out in the Updated EM&A Manual.

ET Certification

I hereby certify that the above referenced document/plan complies with the above referenced condition of FEP-01/558/2018/A, FEP-02/558/2018/A & FEP-03/558/2018/B.

Mr Raymond Chow,

Environmental Team Leader:

Date:

15 April 2024

IEC Verification

I hereby verify that the above referenced document/plan complies with the above referenced condition of FEP-01/558/2018/A, FEP-02/558/2018/A & FEP-03/558/2018/B.

Lydin Clake

Ms Lydia Chak,

Independent Environmental Checker:

Date:

15 April 2024

CONTENTS

EXE	CUTIVE	SUMMARY	1						
1.	INTRO	DUCTION	2						
1.1	BACKG	BACKGROUND 2							
1.2	STRUCT	URE OF THE REPORT	2						
2.	OPERA	TIONAL PHASE WATER QUALITY MONITORING	4						
2.1	MONITO	DRING LOCATIONS	4						
2.2	MONITO	DRING METHODOLOGY	4						
230	2.2.1 2.2.2 2.2.3 2.2.4	Monitoring Parameters and Frequency Monitoring Equipment Operational/ Analytical Procedures Action and Limit Levels for Marine Water Quality Monitoring EQUIREMENTS	4 5 6 6						
2.5									
	2.3.1 2.3.2 2.3.3 2.3.4	Caliberation of In-situ Instruments Decontamination Procedures Sampling Management and Supervision Quality Control Measures for Sample Testing	10 10 10 10						
2.4	OPERAT	ION PHASE WATER QUALITY MONITORING RESULTS	10						
2.5	SUMMA	RY OF EXCEEDANCES OF THE ENVIRONMENTAL QUALITY PERFORMANCE LIMIT	12						
2.6		RY OF ENVIRONMENTAL COMPLAINTS, NOTIFICATION OF SUMMONS AND SSFUL PROSECUTION	12						
3.	CONCL	ILSION	13						
ANN	EX A	CALIBRATION CERTIFICATES							
ANN	ANNEX B MONITORING SCHEDULE								
ANN	NNEX C OPERATION PHASE WATER QUALITY MONITORING RESULTS								
ANN	NNEX D GRAPHICAL PRESENTATION OF OPERATION PHASE WATER QUALITY MONITORING RESULTS								

LIST OF TAE	LIST OF TABLES						
TABLE 2.1	LOCATION OF WATER QUALITY MONITORING STATIONS	4					
TABLE 2.2	WATER QAULITY MONITORING PARAMETERS AND FREQUENCY	5					
TABLE 2.3	WATER QAULITY MONITORING EQUIPMENT	6					
TABLE 2.4	ACTION AND LIMIT LEVELS FOR OPERATION PHASE WATER QUALITY MONITORING	3 7					
TABLE 2.5	EVENT AND ACTION PLAN FOR OPERATION PHASE WATER QUALITY MONITORING	8					
TABLE 2.6	DETAILS OF EXCEEDANCES FOR OPERATIONAL PHASE WATER QUALITY MONITORING	11					

VERSION: 0

LIST OF FIGURES

FIGURE 1.1 INDICATIVE LOCATION OF KEY PROJECT COMPONENTS

FIGURE 2.1 WATER QUALITY MONITORING LOCATIONS



CLIENT: CAPCO, HK Electric, HKLTL
PROJECT NO: 0505354 DATE: 12 April 2024 VERSION: 0 Page ii

EXECUTIVE SUMMARY

To support the increased use of natural gas in Hong Kong from 2020 onwards, Castle Peak Power Company Limited (CAPCO) and The Hongkong Electric Co., Ltd. (HK Electric) have identified that the development of an offshore liquefied natural gas (LNG) receiving terminal in Hong Kong using Floating Storage and Regasification Unit (FSRU) technology ('the Project') presents a viable additional gas supply option that will provide energy security through access to competitive gas supplies from world markets. The Project involves the construction and operation of an offshore LNG import facility to be located in the southern waters of Hong Kong, a double berth jetty, and subsea pipelines that connect to the gas receiving stations (GRS) at the Black Point Power Station (BPPS) and the Lamma Power Station (LPS). The Project commenced operation on 3 July 2023. In accordance with the Updated EM&A Manual of the Project, operation phase water quality monitoring is undertaken during the first year of operation for the Project. This is the water quality monitoring report presenting the operation phase water quality monitoring carried out between January and March 2024.

During the reporting period, operation phase water quality monitoring was conducted at three monitoring locations once per week for 13 sessions between 2 January and 28 March 2024. There were no Project-related Action and Limit Level exceedances for the operation phase water quality monitoring in the reporting period. Overall, deterioration of water quality and indirect impacts at water and ecological sensitive receivers were not detected. The operation of the Project did not result in unacceptable water quality impacts to the nearby water and ecological sensitive receivers, which aligns with the EIA study predictions.

There were no environmental complaints, notification of summons and successful prosecutions recorded for the operation of the Project in the reporting period.

The monitoring activities conducted in the reporting period have been reviewed and are considered effective. As such, no change to the monitoring methodology is recommended. Based on the EM&A findings for the reporting period, the environmental performance for the operation of the Project is generally in line with the EIA predictions and considered acceptable.

1. INTRODUCTION

1.1 BACKGROUND

To support the increased use of natural gas in Hong Kong from 2020 onwards, Castle Peak Power Company Limited (CAPCO) and The Hongkong Electric Co., Ltd. (HK Electric) have identified that the development of an offshore liquefied natural gas (LNG) receiving terminal in Hong Kong using Floating Storage and Regasification Unit (FSRU) technology ('the Project') presents a viable additional gas supply option that will provide energy security through access to competitive gas supplies from world markets. The Project involves the construction and operation of an offshore LNG import facility to be located in the southern waters of Hong Kong, a double berth jetty, and subsea pipelines that connect to the gas receiving stations (GRS) at the Black Point Power Station (BPPS) and the Lamma Power Station (LPS).

The Environmental Impact Assessment (EIA) Report for the Project was submitted to the Environmental Protection Department (EPD) of the HKSAR Government in May 2018. The EIA Report (EIAO Register No. AEIAR-218/2018) was approved by EPD and the associated Environmental Permit (EP) (EP-558/2018) was issued in October 2018.

An application for Further Environmental Permits (FEPs) were made on 24 December 2019 to demarcate the works between the different parties. The following FEPs were issued on 17 January 2020 and the EP under EP-558/2018 was surrendered on 5 March 2020.

- the double berth jetty at LNG Terminal under the Hong Kong LNG Terminal Limited (HKLTL), joint venture between CAPCO and HK Electric (FEP-01/558/2018/A) (1) construction commenced on 27 November 2020;
- the subsea gas pipeline for the BPPS and the associated GRS in the BPPS under CAPCO (FEP-03/558/2018/B) (2) construction commenced on 23 September 2020; and
- the subsea gas pipeline for the LPS and the associated GRS in the LPS under HK Electric (FEP-02/558/2018/A) (3) construction commenced on 13 December 2020.

The location of these components is shown in *Figure 1.1*.

The Project commenced operation on 3 July 2023. This is the quarterly report for the operation phase water quality monitoring for the LNG Terminal which summarises the key monitoring results for the reporting period of January to March 2024 in accordance with the *Updated EM&A Manual* of the Project.

1.2 STRUCTURE OF THE REPORT

The remainder of the report is structured as follows:

⁽³⁾ Application for variation of an environmental permit for FEP-02/558/2018 was undertaken and the latest FEP (FEP-02/558/2018/A) was issued on 22 December 2020.




⁽¹⁾ Application for variation of an environmental permit for FEP-01/558/2018 was undertaken and the latest FEP (FEP-01/558/2018/A) was issued on 6 November 2020.

⁽²⁾ Application for variation of an environmental permit for FEP-03/558/2018/A was undertaken and the latest FEP (FEP-03/558/2018/B) was issued on 25 August 2021.

- Section 2 details the monitoring locations, monitoring methodology, QA/QC requirements, and the monitoring results;
- Section 3 provides the conclusion of this operation phase water quality monitoring.

CLIENT: CAPCO, HK Electric, HKLTL
PROJECT NO: 0505354 DATE: 12 April 2024

VERSION: 0







2. OPERATIONAL PHASE WATER QUALITY MONITORING

In accordance with the *Updated EM&A Manual* of the Project, operation phase water quality monitoring would be conducted once a week for one year after operation of the LNG Terminal. Details of the operation phase water quality monitoring under this Project are presented in the following sections.

2.1 MONITORING LOCATIONS

Operation phase water quality monitoring was conducted at 3 monitoring stations around the LNG Terminal, comprising 1 sensitive receiver station, 1 ebb-tide control station and 1 flood-tide control station. The locations of the monitoring stations are presented in *Figure 2.1*. The coordinates and description of monitoring stations are summarised in *Table 2.1*.

TABLE 2.1 LOCATION OF WATER QUALITY MONITORING STATIONS

Station	Easting	Northing	Description
IM6	814073	802029	Boundary of South Lantau Marine Park
E2	813367	808213	Control Station for Ebb Tide
F3	815032	801161	Control Station for Flood Tide

2.2 MONITORING METHODOLOGY

2.2.1 MONITORING PARAMETERS AND FREQUENCY

The parameters that have been selected for measurement *in situ* and in the laboratory are those that were either determined in the EIA to be those with the highest potential to be affected by the Project or are a standard check on water quality conditions. *Table 2.2* summarises the monitoring parameters, monitoring period and frequencies of the water quality monitoring. The measurement of monitoring parameters followed the standard methods and detection limit requirements as stated in *Table 5.2* of the *Updated EM&A Manual*.

TABLE 2.2 WATER QAULITY MONITORING PARAMETERS AND FREQUENCY

Monitoring Station	Parameters	Depth	Frequency and Replication
Sensitive Receiver Station IM6 Control Stations Ebb tide - E2 Flood tide - F3	 Dissolved Oxygen (DO) (mg/L) Dissolved Oxygen Saturation (DOS) (%) Temperature (°C) pH Turbidity (NTU) Salinity (ppt) Water depth (m) Total Residual Chlorine (TRC) (mg/L) Suspended Solid (SS) (mg/L) Total Inorganic Nitrogen (TIN) (mg/L) 5-day Biochemical Oxygen Demand (BOD₅) (mg/L) 	 Three water depths: 1 m below sea surface, middepth and 1 m above seabed. If the water depth is less than 3 m, mid-depth sampling only. If water depth less than 6 m, mid-depth would be omitted. 	 First year of operation water quality monitoring: one day per week, at mid-flood and mid-ebb tides, for one year upon the commencement of operation of the LNG Terminal. The interval between two sets of monitoring shall not be less than 36 hours. Two replicates of in-situ measurements and water samples at each depth at each station.

In addition to the water quality parameters, other relevant data were also measured and recorded in Water Quality Monitoring Logs, including the location of the monitoring stations, water depth, time, weather conditions, sea conditions, tidal state, current direction and velocity, special phenomena and work activities undertaken around the monitoring and works area that may influence the monitoring results.

2.2.2 MONITORING EQUIPMENT

Table 2.3 summarises the equipment used in the monitoring works. All the monitoring equipment complied with the requirements as set out in the *Updated EM&A Manual*.



CLIENT: CAPCO, HK Electric, HKLTL

PROJECT NO: 0505354 DATE: 12 April 2024 VERSION: 0

TABLE 2.3 WATER QAULITY MONITORING EQUIPMENT

Equipment	Brand and Model
Water Sampling Equipment	SBE 32 Carousel Water Sampler
Positioning Device	Hemisphere Vector V500
Water Depth Gauge	Knudsen 320M Single Beam Echo Sounder
Equipment for Dissolved Oxygen, Temperature, Turbidity, pH and Salinity measurements	YSI 6820, S/N: MPP16, MPP57, MPP15, MPP46 (Note 1)
Total Residual Chlorine	Hanna Instruments (Model HI761)
Equipment for Current Velocity and Direction measurements	Teledyne RDI Workhorse Sentinel ADCP

Note 1

MPP16 was deployed for the monitoring conducted between 2 January 2024 and 15 February 2024, except 31 January and 8 February 2024;

MPP57 was deployed for the monitoring conducted on 31 January 2024;

MPP15 was deployed for the monitoring conducted on 8 February 2024;

MPP46 was deployed for the monitoring conducted between 23 February 2024 and 28 March 2024.

2.2.3 OPERATIONAL/ ANALYTICAL PROCEDURES

At each monitoring station, two consecutive measurements of DO level, DO Saturation, Temperature, Turbidity, Salinity and pH were taken at each sampling depth. Where the difference in the value between the first and second readings of each set was more than 25% of the value of the first reading, the reading was discarded, and further readings were taken. Two water samples were collected for laboratory analysis of SS, TIN and BOD₅. Following sample collection, water samples were stored in high density polythene bottles (1L) with no preservatives added, packed in ice (cooled to 4°C without being frozen) and kept in dark during both on-site temporary storage and transfer to the testing laboratory. The samples were delivered to the laboratory as soon as possible and the laboratory determination works started within 24 hours after collection of the water samples.

The testing of SS, TIN and BOD_5 for all monitoring stations was conducted by a Hong Kong Laboratory Accreditation Scheme (HOKLAS) accredited laboratory, ALS Technichem (HK) Pty Ltd. (HOKLAS Registration No. 066). Comprehensive quality assurance and control procedures were in place in order to ensure quality and consistency in results.

2.2.4 ACTION AND LIMIT LEVELS FOR MARINE WATER QUALITY MONITORING

The Action and Limit Levels for operation phase water quality monitoring have been established with reference to *Table 5.5 of the Updated EM&A Manual*. Action and Limit Levels of key assessment parameters for operation phase marine water quality monitoring are summarised in *Table 2.4* which have been agreed with EPD.






TABLE 2.4 ACTION AND LIMIT LEVELS FOR OPERATION PHASE WATER QUALITY MONITORING

Parameters	Action Level	Limit Level				
First-year Operation Phase Water Quality Monitoring						
DO in mg L ^{-1 a}	Surface and Middle 4.0 mg L ⁻¹	Surface and Middle 3.0 mg L ⁻¹				
	Bottom 2.2 mg L ⁻¹	Bottom 1.5 mg L ⁻¹				
Water Temperature in °C (Depth-averaged b) c	± 1.5 °C of baseline data, and ± 1.5 °C of the relevant control station's water temperature at the same tide of the same day	± 2.0 °C of baseline data, and ± 2.0 °C of the relevant control station's water temperature at the same tide of the same day				
Turbidity in NTU (Depth-averaged ^b) ^c	18.3 NTU, and 120% of the relevant control station's turbidity at the same tide of the same day	30.8 NTU, and 130% of the relevant control station's turbidity at the same tide of the same day				
SS in mg L ⁻¹ (Depth-averaged ^b) ^c	17.5 mg L ⁻¹ , and 120% of the relevant control station's SS at the same tide of the same day	29.5 mg L ⁻¹ , and 130% of the relevant control station's SS at the same tide of the same day				
TIN in mg L ⁻¹ (Depth-averaged ^b) ^c	0.5 mg L ⁻¹ , and 120% of the relevant control station's TIN at the same tide of the same day	0.8 mg L ⁻¹ , and 130% of the relevant control station's TIN at the same tide of the same day				
BOD ₅ in mg L ⁻¹ (Depth-averaged ^b) ^c	1.9 mg L ⁻¹ , and 120% of the relevant control station's BOD5 at the same tide of the same day	2.8 mg L ⁻¹ , and 130% of the relevant control station's BOD5 at the same tide of the same day				
TRC in mg L ⁻¹ (Depth-averaged ^b) ^c	0.02 mg L ⁻¹	0.02 mg L ⁻¹				

Notes:

- a. For DO, non-compliance of the water quality limits occurs when monitoring result is lower than the limits.
- b. "Depth-averaged" is calculated by taking the arithmetic means of reading of all three depths.
- c. For water temperature, salinity, SS, turbidity, BOD_5 , TIN and TRC, non-compliance of the water quality limits occurs when monitoring result is higher than the limits.

The Event and Action Plan for operation phase water quality monitoring is provided in *Table* 2.5.

VERSION: 0

TABLE 2.5 EVENT AND ACTION PLAN FOR OPERATION PHASE WATER QUALITY MONITORING

Event	Action					
	ET	IEC	Contractor(s)	Project Proponents		
Action Level being exceeded by one sampling day	 Repeat in-situ measurement to confirm findings; Check monitoring data, plant, equipment and Contractor(s)'s working methods; Identify source(s) of impact and record in notification of exceedance; Inform IEC, Contractor(s) and Project Proponents. 	Check monitoring data submitted by ET and Contractor(s)'s working methods.	 Confirm receipt of notification of exceedance in writing; Check plant and equipment and rectify unacceptable practice. 	Confirm receipt of notification of exceedance in writing.		
Action Level being exceeded by two or more consecutive sampling days	 Repeat in-situ measurement to confirm findings; Check monitoring data, plant, equipment and Contractor(s)'s working methods; Identify source(s) of impact and record in notification of exceedance; Inform IEC, Contractor(s) and Project Proponents; Discuss with IEC and Contractor(s) on additional mitigation measures and ensure that they are implemented. 	1. Check monitoring data submitted by ET and Contractor(s)'s working methods; 2. Discuss with ET and Contractor(s) on additional mitigation measures and advise Project Proponents accordingly; 3. Assess the effectiveness of the implemented mitigation measures.	 Confirm receipt of notification of exceedance in writing; Check plant and equipment and rectify unacceptable practice; Consider changes of working methods; Discuss with ET and IEC on additional mitigation measures and propose them to Project Proponents within 3 working days; Implement the agreed mitigation measures. 	 Confirm receipt of notification of exceedance in writing; Discuss with the IEC on the proposed additional mitigation measures and agree on the mitigation measures to be implemented; Ensure additional mitigation measures are properly implemented. 		



Event	Action						
	ET	IEC	Contractor(s)	Project Proponents			
Limit Level being exceeded by one sampling day	 Repeat in situ measurement to confirm findings; Check monitoring data, plant, equipment and Contractor(s)'s working methods; Identify source(s) of impact and record in notification of exceedance; Inform IEC, Contractor(s), Project Proponents and EPD; Discuss with IEC and Contractor(s) on additional mitigation measures and ensure that they are implemented. 	 Check monitoring data submitted by ET and Contractor(s)'s working methods; Discuss with ET and Contractor(s) on additional mitigation measures and advise Project Proponents accordingly; Assess the effectiveness of the implemented mitigation measures. 	 Confirm receipt of notification of exceedance in writing; Check plant and equipment and rectify unacceptable practice; Critically review the need to change working methods; Discuss with ET and IEC on additional mitigation measures and propose them to Project Proponents within 3 working days; Implement the agreed mitigation measures. 	 Confirm receipt of notification of exceedance in writing; Discuss with the IEC on the proposed additional mitigation measures and agree on the mitigation measures to be implemented; Ensure additional mitigation measures are properly implemented; Request Contractor(s) to critically review the working methods. 			
Limit Level being exceeded by two or more consecutive sampling days	 Repeat in situ measurement to confirm findings; Check monitoring data, plant, equipment and Contractor(s)'s working methods; Identify source(s) of impact and record in notification of exceedance; Inform IEC, Contractor(s), Project Proponents and EPD; Discuss with IEC and Contractor(s) on additional mitigation measures and ensure that they are implemented. 	1. Check monitoring data submitted by ET and Contractor(s)'s working methods; 2. Discuss with ET and Contractor(s) on additional mitigation measures and advise Project Proponents accordingly; 3. Assess the effectiveness of the implemented mitigation measures.	 Confirm receipt of notification of exceedance in writing; Check plant and equipment and rectify unacceptable practice; Critically review the need to change working methods; Discuss with ET and IEC on additional mitigation measures and propose them to Project Proponents within 3 working days; Implement the agreed mitigation measures; As directed by Project Proponents, slow down or stop all or part of the marine construction works until no exceedance of Limit Level. 	 Confirm receipt of notification of exceedance in writing; Discuss with the IEC on the proposed additional mitigation measures and agree on the mitigation measures to be implemented; Ensure additional mitigation measures are properly implemented; Request Contractor(s) to critically review the working methods; Consider and instruct, if necessary, the Contractor(s) to slow down or to stop all or part of the marine construction works until no exceedance of Limit Level. 			

ERM CLIENT: CAPCO, HK Electric, HKLTL
PROJECT NO: 0505354 DATE: 12 April 2024 VERSION: 0

2.3 QA/QC REQUIREMENTS

2.3.1 CALIBERATION OF IN-SITU INSTRUMENTS

In situ monitoring equipment for the measurement of DO, Temperature, Turbidity, pH and Salinity was checked, calibrated and certified by a laboratory accredited under HOKLAS before use, while the test kit for TRC was checked against the calibration check set provided by the manufacturer before commencement of monitoring. Copies of the calibration certificates for the measuring equipment for DO, Temperature, Turbidity, pH and Salinity are attached in **Annex A**. The *in situ* monitoring equipment for the measurement of DO, Temperature, Turbidity, pH and Salinity was subsequently re-calibrated every three months throughout the water quality monitoring. Responses of sensors and electrodes were checked with certified standard solutions before each use. Wet bulb calibrations for dissolved oxygen meter were carried out before commencement of monitoring and after completion of all measurements each day.

On-site calibration of field equipment followed the "Guide to On-Site Test Methods for the Analysis of Waters", BS 1427: 2009. Sufficient stocks of spare parts were maintained for replacements when necessary. Backup monitoring equipment was also made available to ensure monitoring could proceed uninterrupted even when equipment is under maintenance, calibration etc.

2.3.2 DECONTAMINATION PROCEDURES

Water sampling equipment used during the course of the monitoring was decontaminated by manual washing and rinsed with clean seawater/distilled water after each sampling event. All disposable equipment was discarded after sampling.

2.3.3 SAMPLING MANAGEMENT AND SUPERVISION

All sampling bottles were labelled with the sample ID (including the indication of sampling station and tidal stage e.g. IM6_ME_S_R1), laboratory number and sampling date. All water samples were handled under chain of custody protocols and relinquished to the laboratory representatives at locations specified by the laboratory.

2.3.4 QUALITY CONTROL MEASURES FOR SAMPLE TESTING

The sample testing was performed by ALS Technichem (HK) Pty Ltd. The following quality control programme was performed by the laboratory for every batch of 20 samples:

- One method blank; and
- One set of quality control (QC) samples (including method QC and sample duplicate).

2.4 OPERATION PHASE WATER QUALITY MONITORING RESULTS

Operation phase water quality monitoring was conducted at three monitoring locations once per week for 13 sessions between 2 January and 28 March 2024. The detailed monitoring schedule is shown in **Annex B**. The monitoring results with weather and sea conditions at each monitoring day are shown in **Annex C**. Graphical presentation of water quality monitoring results is given in **Annex D**. During the monitoring sessions, the major activity on site was the operation of the LNG Terminal and no observable pollution source was recorded at



the monitoring stations. No other external factors (e.g. surface runoff from nearby landmass, adverse weather) were identified that might affect water quality at the monitoring stations during the monitoring period.

An action Level exceedance was recorded for operation phase water quality monitoring in the reporting period. Investigation on the exceedances was conducted and summarised in *Table* **2.6**.

TABLE 2.6 DETAILS OF EXCEEDANCES FOR OPERATIONAL PHASE WATER QUALITY MONITORING

Date	Tide	Parameter	Monitoring Station	Level of Exceedance	Investigation
23 February 2024	Mid-ebb	Depth- Average 5-day biochemical oxygen demand (BOD5)		Action	Discharge of cooled seawater for the operation of the regasification system was undertaken on 23 February 2024. According to the information provided by HKLTL and the operator, the flow rate of the cooled seawater discharge was about 5,000 m³/hr. In addition, there was effluent discharge from the sewage treatment plant with a flow rate less than 10 m³/day. Discharge of seawater for the maintenance of firewater operation system was undertaken on 23 February 2024. According to the information provided by HKLTL and the operator, the flow rate of the seawater discharge was about 15 m³/hr. The exceedance in 5-day biochemical oxygen demand (BOD5) is unlikely due to the operation of the Project, in view of the following: The seawater and effluent discharge complied with the requirements as stated in the licence under the Water Pollution Control Ordinance. With reference to the marine water quality data recorded by EPD since 1989 at the station located closest to the
					Project (i.e. SM17), fluctuations of BOD5 were recorded with ranges between <0.1 mg/L and 7.3mg/L. The current measured level is within the



CLIENT: CAPCO, HK Electric, HKLTL

PROJECT NO: 0505354 DATE: 12 April 2024 VERSION: 0 Page 11

Date	Tide	Parameter	Monitoring Station	Level of Exceedance	Investigation
					ranges of the historical dataset and thus considered to be sporadic event and characteristics of water quality in this area of Hong Kong.

Based on the investigation results above, the exceedance was not Project-related.

Nevertheless, HKLTL and the operator were reminded to ensure mitigation measures for water quality impacts as set out in the Updated EM&A Manual are fully and properly implemented. In addition, the discharge of effluent shall follow the requirements as stated in the licence under the Water Pollution Control Ordinance.

Overall, deterioration of water quality and indirect impacts at water and ecological sensitive receivers were not detected. The operation of the Project did not result in unacceptable water quality impacts to the nearby water and ecological sensitive receivers, which aligns with the EIA study predictions.

2.5 SUMMARY OF EXCEEDANCES OF THE ENVIRONMENTAL QUALITY PERFORMANCE LIMIT

There were no Project related Action and Limit Level exceedances for operation phase water quality monitoring in the reporting period.

2.6 SUMMARY OF ENVIRONMENTAL COMPLAINTS, NOTIFICATION OF SUMMONS AND SUCCESSFUL PROSECUTION

There were no environmental complaints, notification of summons and successful prosecutions recorded for the operation of the Project in the reporting period.

ERM

CONCULSION

This is the quarterly report for the operation phase water quality monitoring for the LNG Terminal which summarises the key monitoring results for the reporting period of January to March 2024 in accordance with the *Updated EM&A Manual* of the Project.

Operation phase water quality monitoring was conducted at three monitoring locations once per week for 13 sessions between 2 January and 28 March 2024. There were no Project related Action and Limit Level exceedances for operation phase water quality monitoring in the reporting period. Overall, deterioration of water quality and indirect impacts at water and ecological sensitive receivers were not detected. The operation of the Project did not result in unacceptable water quality impacts to the nearby water and ecological sensitive receivers, which aligns with the EIA study predictions.

There were no environmental complaints, notification of summons and successful prosecutions recorded for the operation of the Project in the reporting period.

The monitoring activities conducted in the reporting period have been reviewed and are considered effective. As such, no change to the monitoring methodology is recommended. Based on the EM&A findings for the reporting period, the environmental performance for the operation of the Project is generally in line with the EIA predictions and considered acceptable.



ANNEX A CALIBRATION CERTIFICATES



ALS Technichem (HK) Pty Ltd

11/F., Chung Shun Knitting Centre, 1 - 3 Wing Yip Street,

Kwai Chung, N.T., Hong Kong **T:** +852 2610 1044

F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: LAM MEI SHING WORK ORDER: HK2346633

CLIENT: EGS (ASIA) LTD

ADDRESS: 15/F., NORTH POINT INDUSTRIAL BUILDING, **SUB-BATCH:** (

499 KING'S ROAD, NORTH POINT, HONG KONG

LABORATORY: HONG KONG

DATE RECEIVED: 21-Nov-2023 **DATE OF ISSUE:** 22-Nov-2023

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: Multifunctional Meter Service Nature: Performance Check

Scope: Dissolved Oxygen, pH Value, Turbidity, Salinity and Temperature

Brand Name/ Model No.: [YSI]/ [6820-C-M]

Serial No./ Equipment No.: [02J0058-AA]/ [MPP15]
Date of Calibration: 21-November-2023

16:5

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

WORK ORDER: HK2346633

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820-C-M]

Serial No./ Equipment No.:

[02J0058-AA]/[MPP15]

Date of Calibration:

21-November-2023

PARAMETERS:

Dissolved Oxygen

Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.86	2.87	+0.01
4.79	4.87	+0.08
6.80	6.88	+0.08
	Tolerance Limit (mg/L)	±0.20

pH Value

Method Ref: APHA (23rd edition), 4500H: B

Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)
4.0	3.89	-0.11
7.0	6.98	-0.02
10.0	10.17	+0.17
	Tolerance Limit (pH unit)	±0.20

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

WORK ORDER: HK2346633

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820-C-M]

Serial No./

[02J0058-AA]/ [MPP15]

Equipment No.: Date of Calibration:

21-November-2023

PARAMETERS:

Turbidity

Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.0	
4	4.1	+2.5
40	39.5	-1.3
80	80.1	+0.1
	Tolerance Limit (%)	±10.0

Salinity

Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.00	
10	9.58	-4.2
20	19.07	-4.7
30	28.53	-4.9
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

WORK ORDER: HK2346633

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/

[YSI]/[6820-C-M]

Model No.: Serial No./

Equipment No.:

[02J0058-AA]/[MPP15]

Date of Calibration:

21-November-2023

PARAMETERS:

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

<u> </u>		
Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
11.0	10.51	-0.5
20.0	19.61	-0.4
41.0	41.16	+0.2
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris



ALS Technichem (HK) Pty Ltd

11/F., Chung Shun Knitting Centre, 1 - 3 Wing Yip Street,

Kwai Chung, N.T., Hong Kong **T:** +852 2610 1044

F: +852 2610 1044 F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: LAM MEI SHING WORK ORDER: HK2346638

CLIENT: EGS (ASIA) LTD

ADDRESS: 15/F., NORTH POINT INDUSTRIAL BUILDING, **SUB-BATCH:** 0

499 KING'S ROAD, NORTH POINT, HONG KONG

LABORATORY: HONG KONG

DATE RECEIVED: 21-Nov-2023 **DATE OF ISSUE:** 22-Nov-2023

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: Multifunctional Meter Service Nature: Performance Check

Scope: Dissolved Oxygen, pH Value, Turbidity, Salinity and Temperature

Brand Name/ Model No.: [YSI]/ [6820-C-M]

Serial No./ Equipment No.: [02J0058-AB]/ [MPP16]
Date of Calibration: 21-November-2023

16:5

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

WORK ORDER: HK2346638

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820-C-M]

Serial No./ Equipment No.:

[02J0058-AB]/[MPP16]

Date of Calibration:

21-November-2023

PARAMETERS:

Dissolved Oxygen

Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.94	2.89	-0.05
5.20	5.23	+0.03
7.63	7.68	+0.05
	Tolerance Limit (mg/L)	±0.20

pH Value

Method Ref: APHA (23rd edition), 4500H: B

Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)
4.0	3.92	-0.08
7.0	6.94	-0.06
10.0	10.15	+0.15
	Tolerance Limit (pH unit)	±0.20

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

WORK ORDER: HK2346638

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820-C-M]

Serial No./ Equipment No.:

[02J0058-AB]/[MPP16]

Date of Calibration:

21-November-2023

PARAMETERS:

Turbidity

Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.0	
4	3.9	-2.5
40	38.7	-3.2
80	78.6	-1.8
	Tolerance Limit (%)	±10.0

Salinity

Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.00	
10	9.56	-4.4
20	19.04	-4.8
30	28.46	-5.1
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

WORK ORDER: HK2346638

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/

[YSI]/[6820-C-M]

Model No.: Serial No./

Equipment No.:

[02J0058-AB]/[MPP16]

Date of Calibration: 21-November-2023

PARAMETERS:

Temperature

Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
11.5	11.45	-0.1
20.0	19.76	-0.2
40.0	40.02	+0.0
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris



ALS Technichem (HK) Pty Ltd

11/F., Chung Shun Knitting Centre, 1 - 3 Wing Yip Street,

Kwai Chung, N.T., Hong Kong **T:** +852 2610 1044

F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: LAM MEI SHING WORK ORDER: HK2346640

CLIENT: EGS (ASIA) LTD

ADDRESS: 15/F., NORTH POINT INDUSTRIAL BUILDING, **SUB-BATCH:** (

499 KING'S ROAD, NORTH POINT, HONG KONG

LABORATORY: HONG KONG

DATE RECEIVED: 21-Nov-2023 **DATE OF ISSUE:** 22-Nov-2023

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: Multifunctional Meter Service Nature: Performance Check

Scope: Dissolved Oxygen, pH Value, Turbidity, Salinity and Temperature

Brand Name/ Model No.: [YSI]/ [6920 V2-2]
Serial No./ Equipment No.: [16L100580]/ [MPP57]
Date of Calibration: 21-November-2023

16:5

Ms. Lin Wai Yu, Iris Assistant Manager - Inorganics

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

WORK ORDER: HK2346640

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6920 V2-2]

Serial No./ Equipment No.:

[16L100580]/[MPP57]

Date of Calibration: 21-November-2023

PARAMETERS:

Dissolved Oxygen

Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.95	2.95	+0.00
5.04	4.89	-0.15
7.64	7.63	-0.01
	Tolerance Limit (mg/L)	±0.20

pH Value Method Ref: APHA (23rd edition), 4500H: B

Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)
4.0	3.91	-0.09
7.0	6.96	-0.04
10.0	10.19	+0.19
	Tolerance Limit (pH unit)	±0.20

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

WORK ORDER: HK2346640

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6920 V2-2]

Serial No./ Equipment No.:

[16L100580]/[MPP57]

Date of Calibration:

21-November-2023

PARAMETERS:

Turbidity

Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.0	
4	4.2	+5.0
40	41.8	+4.5
80	85.4	+6.8
	Tolerance Limit (%)	±10.0

Salinity

Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.00	
10	9.60	-4.0
20	19.10	-4.5
30	28.65	-4.5
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

WORK ORDER: HK2346640

SUB-BATCH: 0

DATE OF ISSUE: 22-Nov-2023 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6920 V2-2]

Serial No./

[16L100580]/[MPP57]

Equipment No.: Date of Calibration:

21-November-2023

PARAMETERS:

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
11.0	11.08	+0.1
19.5	19.80	+0.3
40.5	40.54	+0.0
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

/ V

Ms. Lin Wai Yu, Iris



ALS Technichem (HK) Pty Ltd

HONG KONG

11/F., Chung Shun Knitting Centre,

1 - 3 Wing Yip Street, Kwai Chung, N.T., Hong Kong

LABORATORY:

T: +852 2610 1044 F: +852 2610 2021 www.alsglobal.com

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

CONTACT: DOMINIC LAI WORK ORDER: HK2406840

CLIENT: EGS (ASIA) LTD

ADDRESS: 15/F., NORTH POINT INDUSTRIAL BUILDING, **SUB-BATCH:** (

499 KING'S ROAD,

NORTH POINT, HONG KONG

DATE RECEIVED: 20-Feb-2024

DATE OF ISSUE: 22-Feb-2024

GENERAL COMMENTS

The performance of the equipment stated in this report is checked with independent reference material and results compared against a calibrated secondary source.

The "Tolerance Limit" quoted is the acceptance criteria applicable for similar equipment used by the laboratory or quoted from relevant international standards.

The "Next Calibration Date" is recommended according to best practice principle as practised by the laboratory or quoted from relevant international standards.

The validity of equipment/ meter performance only applies to the result(s) stated in the report.

This report superseded any previous report(s) with same work order number.

EQUIPMENT INFORMATION

Equipment information (Brand name, Model No., Serial No. and Equipment No.) is provided by client.

Equipment Type: Multifunctional Meter Service Nature: Performance Check

Scope: Dissolved Oxygen, pH Value, Turbidity, Salinity and Temperature

Brand Name/ Model No.: [YSI]/ [6820 V2-M]
Serial No./ Equipment No.: [14A101573]/ [MPP46]
Date of Calibration: 20-February-2024

/ /: 5

Ms. Lin Wai Yu, Iris

Assistant Manager - Inorganics

This report may not be reproduced except with prior written approval from ALS Technichem (HK) Pty Ltd.

WORK ORDER: HK2406840

SUB-BATCH: 0

DATE OF ISSUE: 22-Feb-2024 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820 V2-M]

Serial No./

[14A101573]/[MPP46]

Equipment No.: Date of Calibration:

20-February-2024

Date of Next Calibration: 20-May-2024

PARAMETERS:

Dissolved Oxygen

Method Ref: APHA (23rd edition), 4500O: G

Expected Reading (mg/L)	Displayed Reading (mg/L)	Tolerance (mg/L)
2.94	2.88	-0.06
5.34	5.36	+0.02
7.15	7.19	+0.04
	Tolerance Limit (mg/L)	±0.20

pH Value Method Ref: APHA (23rd edition), 4500H: B

Expected Reading (pH unit)	Displayed Reading (pH unit)	Tolerance (pH unit)
4.0	4.09	+0.09
7.0	6.99	-0.01
10.0	9.98	-0.02
	Tolerance Limit (pH unit)	±0.20

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK2406840

SUB-BATCH: 0

DATE OF ISSUE: 22-Feb-2024 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820 V2-M]

Serial No./ Equipment No.:

[14A101573]/[MPP46]

Date of Calibration:

20-February-2024

Date of Next Calibration: 20-May-2024

PARAMETERS:

Turbidity Method Ref: APHA (23rd edition), 2130B

Expected Reading (NTU)	Displayed Reading (NTU)	Tolerance (%)
0	0.00	
4	3.70	-7.5
40	42.2	+5.5
80	84.8	+6.0
400	-	N/A
800	-	N/A
	Tolerance Limit (%)	±10.0

Salinity Method Ref: APHA (23rd edition), 2520B

Expected Reading (ppt)	Displayed Reading (ppt)	Tolerance (%)
0	0.00	
10	9.91	-0.9
20	19.20	-4.0
30	29.72	-0.9
	Tolerance Limit (%)	±10.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

Assistant Manager - Inorganics

REPORT OF EQUIPMENT PERFORMANCE CHECK/CALIBRATION

WORK ORDER: HK2406840

SUB-BATCH: 0

DATE OF ISSUE: 22-Feb-2024 **CLIENT:** EGS (ASIA) LTD

Equipment Type:

Multifunctional Meter

Brand Name/ Model No.:

[YSI]/[6820 V2-M]

20-February-2024

Serial No./

[14A101573]/[MPP46]

Equipment No.: Date of Calibration: [11/(1010/0]/[[1/111110]

Date of Next Calibration:

20-May-2024

PARAMETERS:

Temperature Method Ref: Section 6 of International Accreditation New Zealand Technical

Guide No. 3 Second edition March 2008: Working Thermometer Calibration Procedure.

Expected Reading (°C)	Displayed Reading (°C)	Tolerance (°C)
10.5	10.69	+0.2
21.0	20.79	-0.2
39.5	39.10	-0.4
	Tolerance Limit (°C)	±2.0

Remark: "Displayed Reading" presents the figures shown on item under calibration / checking regardless of equipment precision or significant figures.

Ms. Lin Wai Yu, Iris

Assistant Manager - Inorganics



ANNEX B MONITORING SCHEDULE

Environmental Team Consultancy Services for the Hong Kong Offshore LNG Terminal Project Operation Phase Water Quality Monitoring (January 2024)

			· · ·		-	
Sunday	Monday			Thursday		Saturday
	1/Jan	2/Jan	3/Jan	4/Jan	5/Jan	6/Jan
		Operation Phase Water				
		Quality Monitoring				
		ebb tide 15:39 - 17:39				
		flood tide 10:26 - 12:06				
7/Jan	8/Jan	9/Jan	10/Jan	11/Jan	12/Jan	13/Jan
		Operation Phase Water				
		Quality Monitoring				
		ebb tide 9:51 - 11:51				
		flood tide 14:32 - 16:32				
		17.02				
14/Jan	15/Jan	16/Jan	17/Jan	18/Jan	19/Jan	20/Jan
		Operation Phase Water				
		Quality Monitoring				
		ebb tide 15:32 - 17:32				
		flood tide 9:48 - 11:48				
		11.10				
21/Jan	22/Jan	23/Jan	24/Jan	25/Jan	26/Jan	27/Jan
					Operation Phase Water Quality	
					Monitoring	
					ebb tide 12:08 - 14:08	
					flood tide 7:01 - 9:01	
					1.01	
28/Jan	29/Jan	30/Jan	31/Jan			
			Operation Phase Water			_
			Quality Monitoring			
			ebb tide 14:40 - 16:40			
			flood tide 8:55 - 10:55			
	!			ļ		

Environmental Team Consultancy Services for the Hong Kong Offshore LNG Terminal Project Operation Phase Water Quality Monitoring (February 2024)

Condon	Manday	Tuesday	Madagaday	Thursday	Friday	Cotumban
Sunday	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday 2/5-b
				1/Feb	2/Feb	3/Feb
4/Feb	5/Feb	6/Feb	7/Feb	8/Feb	9/Feb	10/Feb
171 05	5/1 65	5/1.55	171 00	Operation Phase Water	571 52	10/1 02
				Quality Monitoring		
				ebb tide 10:35 - 12:35		
				flood tide 15:14 - 17:14		
11/Feb	12/Feb	13/Feb	14/Feb	15/Feb	16/Feb	17/Feb
				Operation Phase Water		
				Quality Monitoring		
				ebb tide 15:43 - 17:43		
				flood tide 9:20 - 11:20		
				1100d tide 9.20 - 11.20		
18/Feb	19/Feb	20/Feb	21/Feb	22/Feb	23/Feb	24/Feb
10/1 eb	19/1 65	20/1 60	21/1 65	22/1 60	Operation Phase Water Quality	24/1 60
					Monitoring	
					ebb tide 11:23 - 13:23	
					flood tide 6:03 - 8:03	
25/Feb	26/Feb	27/Feb	28/Feb	29/Feb		
			Operation Phase Water			
			Quality Monitoring			
			ebb tide 13:29 - 15:29			
			flood tide 7:32 - 9:32			
			11000 tide			

Environmental Team Consultancy Services for the Hong Kong Offshore LNG Terminal Project Operation Phase Water Quality Monitoring (March 2024)

Cunday	Monday	Tuesday	Madaaaday	Thursday	Friday	Saturday
Sunday	wonday	Tuesday	Wednesday	Thursday	1/Mar	Saturday 2/Mar
					1/Mar	Z/IVIAI
3/Mar	4/Mar	5/Mar	6/Mar	7/Mar	8/Mar	9/Mar
		-		Operation Phase Water		
				Quality Monitoring		
				ebb tide 9:04 - 11:04		
				flood tide 14:06 - 16:06		
10.01	4404	10.01	40.04	4404	45/04	40/14
10/Mar	11/Mar	12/Mar	13/Mar	14/Mar	15/Mar	16/Mar
				Operation Phase Water		
				Quality Monitoring		
				ebb tide 14:12 - 16:12		
				flood tide 7:47 - 9:47		
17/Mar	18/Mar	19/Mar	20/Mar	21/Mar	22/Mar	23/Mar
				Operation Phase Water		
				Quality Monitoring		
				ebb tide 10:14 - 12:14		
				flood tide 15:04 - 17:04		
24/Mar	25/Mar	26/Mar	27/Mar	28/Mar	29/Mar	30/Mar
24/IVIAI	25/10/81	20/10/21	Z1/IVIai	Operation Phase Water	29/Mai	30/Mai
				Quality Monitoring		
				ebb tide 13:00 - 15:00		
				flood tide 6:43 - 8:43		
31/Mar						



ANNEX C

OPERATION PHASE WATER QUALITY MONITORING RESULTS

Date: 2024/01/02

Tic	. Monitorir	ng Weather	Sea	Sampling	Water Depth	Depth	Current	Current	T	emperature (°	C)	Salinity (ppt)	pl	4	DO Satu	ration (%)	Dissol	ved Oxygen (mg/L)	1	urbidity(NTU)	Total Res	idual Chlorin	e (mg/L)	Suspen	ded Solids (mg/L)	Total Inorg	ganic Nitrog	en (mg/L)	5-day Biochen	nical Oxygen Der	mand (mg/L)
110	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value .	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.46	130 130	20.1	20.1		33.4 33.3	33.3	8.2 8.2	8.2	103.7	104.0	7.7 7.8	7.7	7.7	2.8	2.8		<0.001	<0.001		2.6	2.6		0.09	0.09		<1.0 <1.0	<1.0	
	E2	Fine	Moderate	16:18	9.5	М	0.30	307 346	20.1	20.1	20.0	33.4 33.4	33.4	8.2 8.2	8.2	101.6	101.9	7.6 7.6	7.6	1.1	4.4	4.5	5.7	<0.001	<0.001	<0.001	3.0 2.9	3.0	4.3	0.08	0.08	0.08	<1.0 <1.0	<1.0	<1.0
Mid-	- 6.6					В	0.45 0.13	185 5	20.0 20.0	20.0		33.4 33.4	33.4	8.2 8.2	8.2	102.7 101.5	102.1	7.7 7.6	7.6	7.6	9.0	9.9		<0.001	<0.001		7.0 7.5	7.3		0.08	0.08		<1.0 <1.0	<1.0	
IVIIG-	-00					S	0.66 0.13	178 346	19.9 19.9	19.9		33.4 33.4	33.4	8.1 8.1	8.1	99.2 99.1	99.2	7.4 7.4	7.4	7.4	4.1 4.2	4.2		<0.001 0.004	0.003		3.8 4.2	4.0		0.08	0.08		<1.0 <1.0	<1.0	
	IM6	Fine	Moderate	15:49	17.1	М	1.03	72 335	19.7 19.7	19.7	19.8	33.4 33.4	33.4	8.1 8.1	8.1	98.6 98.5	98.6	7.4 7.4	7.4		5.3 5.1	5.2	5.0	<0.001 <0.001	<0.001	0.002	5.1 5.4	5.3	5.2	0.07 0.07	0.07	0.07	<1.0 <1.0	<1.0	<1.0
						В	0.14 0.05	92 336	19.7 19.7	19.7		33.4 33.4	33.4	8.1 8.1	8.1	99.5 99.1	99.3	7.5 7.4	7.4	7.4	5.5 5.7	5.6		<0.001 <0.001	<0.001		6.1 6.5	6.3		0.06 0.07	0.07		<1.0 <1.0	<1.0	
						s	0.73 0.84	274 300	19.7 19.7	19.7		33.3 33.3	33.3	8.2 8.2	8.2	98.6 98.5	98.6	7.4 7.4	7.4	7.4	4.2 4.1	4.2		<0.001	<0.001		4.2 4.5	4.4		0.07	0.08		<1.0 <1.0	<1.0	
	F3	Cloudy	Rough	10:55	18.0	М	0.27 0.19	323 3	19.7 19.7	19.7	19.7	33.3 33.3	33.3	8.2 8.2	8.2	98.0 98.2	98.1	7.4 7.4	7.4	7.4	6.2 5.6	5.9	9.9	<0.001	<0.001	<0.001	5.4 5.1	5.3	10.6	0.08	0.08	0.08	<1.0 <1.0	<1.0	<1.0
Mi						В	0.17 0.17	9	19.7 19.7	19.7		33.3 33.3	33.3	8.2 8.2	8.2	98.7 98.1	98.4	7.4 7.4	7.4	7.4	19.4 20.0	19.7		<0.001 <0.001	<0.001		21.7 22.4	22.1		0.07	0.07		<1.0 <1.0	<1.0	
Flo	od					s	0.39	190 190	19.7 19.7	19.7		33.4 33.4	33.4	8.1 8.1	8.1	98.7 98.5	98.6	7.4 7.4	7.4	7.4	7.4 7.2	7.3		<0.001 0.003	0.002		8.1 8.6	8.4		0.06 0.06	0.06		<1.0 <1.0	<1.0	
	IM6	Cloudy	Rough	10:33	16.8	М	0.48 0.59	353 56	19.7 19.7	19.7	19.7	33.4 33.4	33.4	8.1 8.1	8.1	98.7 98.7	98.7	7.4 7.4	7.4		9.3 8.4	8.9	8.7	<0.001 <0.001	<0.001	0.001	8.4 8.0	8.2	9.4	0.06 0.05	0.06	0.06	<1.0 <1.0	<1.0	<1.0
						В	0.02	357 357	19.8 19.8	19.8		33.4 33.4	33.4	8.1 8.1	8.1	99.6 99.1	99.4	7.5 7.4	7.5	7.5	10.0	10.1		<0.001	<0.001		11.9	11.7		0.06	0.06		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/01/09

Tide	Monitoring	Weather	Sea	Sampling	Water Depth		Current	Current	Te	mperature (°	C)	Salini	ty (ppt)	F	Н	DO Satu	ration (%)	Dissol	ved Oxygen (mg/L)	Т	urbidity(NTU))	Total Res	idual Chlorin	e (mg/L)	Susper	nded Solids	(mg/L)	Total Inor	ganic Nitrog	en (mg/L)	5-day Biocher	nical Oxygen De	emand (mg/L)
lide	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.81	64	19.3	19.3		33.6	33.6	8.3	8.3	125.1	125.1	9.4	9.4		0.6	0.6		<0.001	<0.001		2.2	2.3		<0.02	<0.02		1.1	1.2	
							0.81	64	19.3			33.6		8.3		125.0		9.4		9.4	0.5			<0.001			2.4			<0.02			1.3		
	E2	Cloudy	Calm	10:37	9.2	M	0.21	42 137	19.2	19.2	19.3	33.6 33.6	33.6	8.3	8.3	123.5	123.7	9.3	9.4		0.5	0.6	0.6	<0.001	<0.001	<0.001	2.5	2.7	2.8	<0.02 <0.02	<0.02	< 0.02	1.3	1.3	1.2
						B	0.24	261	19.2	19.2		33.6	33.6	8.3	8.3	120.7	120.7	9.1	9.1	9.1	0.7	0.7		<0.001	<0.001		3.6	3.5	İ	<0.02	<0.02		<1.0	<1.0	
Mid-Eb							0.19	221	19.2	10.2		33.6	00.0	8.3	0.0	120.7	120.7	9.1	0.1	0.1	0.6	0.7		<0.001	-0.001		3.3	0.0		<0.02	-0.02		<1.0	-1.0	
						s	0.17	114	18.7	18.7		33.8	33.7	8.2 8.2	8.2	102.3	102.3	7.8	7.8	77	1.8	1.8		<0.001	<0.001		3.4	3.3		0.04	0.04		<1.0 <1.0	<1.0	
	IM6	Cloudy	Calm	10:04	17.1	М	0.42	241	18.6 18.6	18.6	18.6	33.8	33.8	8.2 8.2	8.2	100.4	100.5	7.7	7.7	1.1	2.3	2.2	2.5	<0.001	<0.001	0.002	4.0	3.9	3.9	0.04	0.04	0.04	<1.0 <1.0	<1.0	<1.0
							0.35	96	18.6			33.8		8.2		98.0		7.5			3.6			<0.001			4.6		ł	0.04			<1.0		
						B	0.35	96	18.6	18.6		33.8	33.8	8.2	8.2	98.1	98.1	7.5	7.5	7.5	3.5	3.6		0.005	0.003		4.3	4.5		0.05	0.05		<1.0	<1.0	
						s	0.48	286 343	19.8 19.8	19.8		33.5 33.5	33.5	8.2 8.2	8.2	106.7	106.9	8.0 8.0	8.0	7.9	1.5	1.5		<0.001	<0.001		2.2	2.4		0.04	0.05		<1.0 <1.0	<1.0	
	F3	Fine	Calm	14:47	18.2	М	0.53 0.53	28 28	19.4 19.5	19.4	19.5	33.4 33.5	33.5	8.2 8.2	8.2	103.4	104.1	7.8	7.9	7.9	1.6	1.7	1.9	<0.001	<0.001	0.002	3.0 2.6	2.8	2.9	0.04	0.04	0.04	<1.0 <1.0	<1.0	<1.0
Mid-						В	0.07 0.53	129	19.3	19.3		33.5 33.5	33.5	8.1 8.2	8.2	101.2	101.1	7.7	7.6	7.6	2.4	2.6		<0.001	0.003		4.1	3.4		0.04	0.05		<1.0 <1.0	<1.0	
Flood							0.14	334	19.5			33.4		8.1		105.2		7.0			1.7			<0.004			2.9			0.03			<1.0		
1.000						S	0.16	60	19.7	19.6		33.4	33.4	8.1	8.1	106.3	105.8	8.0	8.0	7.8	1.8	1.8		<0.001	<0.001		2.6	2.8		0.04	0.04		<1.0	<1.0	
	IM6	Fine	Calm	14:32	17.2	М	0.68	222 264	19.3 19.3	19.3	19.4	33.5 33.5	33.5	8.1 8.1	8.1	102.1 102.9	102.5	7.7	7.8		1.9	1.9	2.8	<0.001	<0.001	<0.001	3.6	3.5	5.4	0.05	0.05	0.05	<1.0 <1.0	<1.0	<1.0
						В	0.25 0.25	74 74	19.3 19.3	19.3		33.5 33.5	33.5	8.1 8.1	8.1	100.7 100.5	100.6	7.6 7.6	7.6	7.6	4.7 4.9	4.8		<0.001 <0.001	<0.001		10.6 9.0	9.8		0.05 0.05	0.05		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/01/16

	I Maria Maria			I 0	LW-4 B	I D	T 0				0)	0.0.0		nl		DO 0-4-		Discort						T-4-1 D-					(B)	T. T. L. I. I		(E des Blackes		
Tic	Monitorin		Sea		Water Depth		Current	Current		emperature (°		Salinity (P		DO Satu			lved Oxygen (urbidity(NTU			idual Chlorin			nded Solids			ganic Nitrog			nical Oxygen De	
	Station	Condition	Condition**	Time	(m)	Level ***	, , , ,		Value	Average	DA		Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.25	250	20.2	20.2		32.9	32.9	8.3	8.3	110.2	110.0	8.2	8.2		3.0	3.0		<0.001	<0.001		4.0	3.9		0.08	0.08		<1.0	<1.0	
							0.25	250	20.2			32.9		8.3		109.7		8.2		8.2	2.9			<0.001			3.7			0.08			<1.0		ı .
	E2	Fine	Rough	16:03	9.0	М	0.09	352	20.2	20.2	20.2	32.9	32.9	8.3	8.3	109.2	109.3	8.2	8.2		3.2	3.1	3.1	<0.001	<0.001	< 0.001	4.6	4.8	4.8	0.08	0.08	0.08	<1.0	<1.0	<1.0
			"				0.21	61	20.2			32.9		8.3		109.3		8.2			2.9			<0.001			5.0			0.08			<1.0		, 1
						B	0.15	126	20.2	20.2		32.9	32.9	8.3	8.3	107.6	108.0	8.0	8.1	8.1	3.2	3.2		<0.001	<0.001		5.9	5.7		0.07	0.08		<1.0	<1.0	, !
Mid-8	bb					_	0.28	65	20.2			33.0		8.3		108.3		8.1			3.1			<0.001			5.5			0.08			<1.0		
						s	0.42	338	19.9	19.9		33.3	33.3	8.2	8.2	108.2	108.2	8.1	8.1		1.9	1.9		<0.001	<0.001		3.7	3.8		0.06	0.05		<1.0	<1.0	, !
							0.42	338	19.9			33.3		8.2		108.1		8.1		8.0	1.8			<0.001			3.9			0.04			<1.0		, !
	IM6	Fine	Rough	15:32	17.0	М	0.22	336	19.9	19.9	19.9	33.5	33.5	8.2	8.2	106.5	106.7	8.0	8.0		3.6	3.3	3.2	<0.001	<0.001	< 0.001	4.4	4.3	4.6	0.04	0.04	0.04	<1.0	<1.0	<1.0
			"				0.11	284	19.9			33.5		8.2		106.8		8.0			3.0			<0.001			4.2			0.04			<1.0		, 1
						В	0.04	152	19.9	19.9		33.6	33.6	8.2	8.2	105.7	105.8	7.9	7.9	7.9	4.1	4.4		<0.001	<0.001		5.8	5.7		0.02	0.02		<1.0	<1.0	, !
_	_	_				_	0.04	152	19.9			33.6		8.2		105.9		7.9			4.6			<0.001			5.6			<0.02			<1.0		
						s	0.68	271	19.9	19.9		33.5	33.5	8.3	8.3	104.3	104.4	7.8	7.8		3.8	3.9		<0.001	<0.001		4.0	4.2		0.02	0.03		<1.0	<1.0	, !
							0.68	271	19.9			33.5		8.3		104.5		7.8		7.8	3.9			<0.001			4.4			0.04			<1.0		, !
	F3	Cloudy	Rough	10:27	18.0	М	0.81	276	19.9	19.9	19.9	33.6	33.6	8.3	8.3	103.7	103.7	7.8	7.8		4.8	4.5	8.2	<0.001	<0.001	< 0.001	6.8	6.6	8.0	0.02	0.02	0.02	<1.0	<1.0	<1.0
			-				0.41	236	19.9			33.6		8.3		103.7		7.8			4.2			<0.001			6.4		ļ	0.02			<1.0		, !
	.					В	0.67	276	19.9	19.9		33.5	33.5	8.3	8.3	103.4	103.6	7.7	7.8	7.7	17.0	16.1		<0.001	<0.001		13.5	13.2		<0.02	< 0.02		<1.0	<1.0	, !
Mic						_	0.53	291	19.9			33.6	_	8.3		103.8		7.8			15.2			<0.001			12.8			<0.02			<1.0		
Flo	od					S	0.52	247	20.0	20.0		33.4	33.4	8.2	8.2	104.9	104.9	7.8	7.8		5.5	5.4		<0.001	0.001		7.4	7.7		0.03	0.04		<1.0	<1.0	, !
							0.52	247	20.0			33.4		8.2		104.8		7.8		7.8	5.2			0.001			7.9			0.05			<1.0		, !
	IM6	Cloudy	Rough	9:58	16	М	0.41	268	20.0	20.0	20.0	33.4	33.4	8.2	8.2	104.6	104.4	7.8	7.8		5.1	5.1	6.0	<0.001	<0.001	0.001	8.7	8.5	9.3	0.05	0.05	0.04	<1.0	<1.0	<1.0
		1 1	1				0.32	218	20.0			33.4		8.2		104.2		7.8			5.0	$\overline{}$		<0.001			8.3		1	0.05			<1.0		
					1	В	0.83	293	20.0	20.0		33.4	33.4	8.2	8.2	104.2	104.1	7.8	7.8	7.8	7.6	7.7		<0.001	<0.001		11.1	11.8		0.03	0.04		<1.0	<1.0	
	1			1	1	1	0.12	339	20.0	1		33.4	- 1	8.2		104.0	ı	7.8	1 1		7.7	I I		<0.001			12.5		I	0.05			<1.0		

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/01/26

Tid		onitoring	Weather	Sea	Sampling	Water Depth		Current	Current	Ter	mperature (°C)	Salinit	(ppt)		pН	DO Satu	ration (%)	Dissol	lved Oxygen	mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	e (mg/L)	Susper	ded Solids ((mg/L)	Total Inorg	anic Nitrog	en (mg/L)	5-day Biocher	nical Oxygen De	emand (mg/L)
l III	' s	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
							s	0.35 0.80	20 33	18.4 18.4	18.4		33.7 33.7	33.7	8.3 8.3	8.3	96.9 97.0	97.0	7.4	7.4	7.5	2.8	2.8		<0.001	<0.001		2.4	2.3		0.06	0.06		<1.0 <1.0	<1.0	
		E2	Cloudy	Moderate	12:38	9.2	М	0.27 0.27	308 308	18.4 18.4	18.4	18.4	33.8 33.8	33.8	8.3 8.3	8.3	97.7 97.3	97.5	7.5 7.5	7.5	7.5	2.7	2.8	2.8	<0.001 <0.001	<0.001	<0.001	2.6 2.5	2.6	2.6	0.08	0.07	0.06	<1.0 <1.0	<1.0	<1.0
Mid-E	bb						В	0.22	329 249	18.4 18.4	18.4		33.8 33.8	33.8	8.3 8.3	8.3	104.2 99.1	101.7	8.0 7.6	7.8	7.8	3.1 2.8	3.0		<0.001	<0.001		2.8 3.0	2.9		0.06	0.06		<1.0 <1.0	<1.0	
MIGS	00						S	0.17 0.17	101 101	19.8 19.8	19.8		34.3 34.3	34.3	8.2 8.2	8.2	98.6 98.8	98.7	7.4	7.4	7.4	2.6	2.5		<0.001	<0.001		3.0 2.8	2.9		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
		IM6	Cloudy	Moderate	12:08	17.0	М	0.15 0.15	326 326	19.8 19.8	19.8	19.8	34.3 34.3	34.3	8.2 8.2	8.2	98.7 98.1	98.4	7.4 7.3	7.3		3.0	3.1	2.8	<0.001	<0.001	<0.001	3.0	3.2	3.3	0.02 <0.02	0.02	0.02	<1.0 <1.0	<1.0	<1.0
							В	0.36 0.36	241 241	19.8 19.8	19.8		34.3 34.3	34.3	8.2 8.2	8.2	101.3 99.6	100.5	7.6 7.4	7.5	7.5	2.8	2.7		<0.001	<0.001		3.6	3.7		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
							S	0.54 0.54	298 298	19.8 19.8	19.8		34.2 34.2	34.2	8.3 8.3	8.3	98.2 97.7	98.0	7.3 7.3	7.3	7.3	2.3 2.5	2.4		<0.001 <0.001	<0.001		4.7	4.6		0.09	0.09		<1.0 <1.0	<1.0	
		F3	Cloudy	Moderate	7:21	17.7	М	0.57 0.15	267 272	19.8 19.8	19.8	19.8	34.2 34.2	34.2	8.3 8.3	8.3	97.9 97.3	97.6	7.3 7.3	7.3	7.5	2.7	2.6	2.8	<0.001 <0.001	<0.001	<0.001	3.4	3.5	3.7	<0.02 <0.02	<0.02	0.04	<1.0 <1.0	<1.0	<1.0
Mid							В	0.53 0.53	301 301	19.8 19.8	19.8		34.2 34.3	34.2	8.3 8.3	8.3	100.5 99.1	99.8	7.5 7.4	7.4	7.4	2.9 3.7	3.3		<0.001	<0.001		3.1 2.7	2.9		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
Floo	d						s	0.09	162 162	19.3 19.3	19.3		34.1 34.1	34.1	8.2 8.2	8.2	96.9 97.2	97.1	7.3 7.3	7.3	7.3	2.7	2.8		<0.001	<0.001		2.9 3.1	3.0		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
		IM6	Cloudy	Moderate	7:06	16.3	М	0.15 0.35	82 235	19.3 19.3	19.3	19.3	34.1 34.2	34.1	8.2 8.2	8.2	97.2 97.0	97.1	7.3 7.3	7.3		3.7	3.6	3.3	<0.001 <0.001	<0.001	<0.001	3.4	3.5	3.4	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
							В	0.1 0.22	15 288	19.3 19.3	19.3		34.1 34.1	34.1	8.2 8.2	8.2	99.6 97.9	98.8	7.5 7.4	7.4	7.4	3.5 3.6	3.6		<0.001 <0.001	<0.001		3.7	3.8		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/01/31

Tide	Monitoring	Weather	Sea	Sampling	Water Depth	Depth	Current	Current	Te	mperature (°0	C)	Salinit	y (ppt)	р	Н	DO Satu	ation (%)	Dissolv	ved Oxygen (mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	ne (mg/L)	Suspe	nded Solids	(mg/L)	Total Inor	ganic Nitrog	en (mg/L)	5-day Biocher	mical Oxygen De	emand (mg/L)
Tiue	Station	Condition	Condition**	Time	(m)	Level **	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.68	34 34	19.6 19.6	19.6		34.2 34.2	34.2	8.4 8.4	8.4	98.1 98.4	98.3	7.3 7.4	7.4	7.3	3.2	3.2		<0.001	<0.001		4.5 4.9	4.7		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	E2	Cloudy	Moderate	15:12	9.0	М	0.21 0.10	43 157	19.5 19.3	19.4	19.4	34.2 34.2	34.2	8.4 8.4	8.4	97.5 96.8	97.2	7.3 7.3	7.3	7.5	3.5	3.7	3.6	<0.001	<0.001	<0.001	5.6 5.2	5.4	5.6	<0.02 <0.02	<0.02	0.02	<1.0 <1.0	<1.0	<1.0
Mid-E	nh.					В	0.30	117 18	19.1 19.1	19.1		34.2 34.2	34.2	8.4 8.4	8.4	96.4 96.2	96.3	7.3 7.3	7.3	7.3	3.8	3.8		<0.001	<0.001		6.7 6.4	6.6		0.03	0.03		<1.0 <1.0	<1.0	
I WILL						S	0.20 0.26	129 4	19.7 19.7	19.7		34.3 34.3	34.3	8.4 8.4	8.4	99.7 99.5	99.6	7.5 7.4	7.4	7.4	1.8	1.8		<0.001	0.005		2.8	2.7		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	IM6	Cloudy	Moderate	14:41	17.0	М	0.52 0.06	171 318	19.3 19.3	19.3	19.3	34.3 34.3	34.3	8.4 8.4	8.4	98.2 98.1	98.2	7.4 7.4	7.4	7.59	2.7	2.6	2.2	<0.001	<0.001	0.002	3.5 3.2	3.4	3.4	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
						В	0.12 0.12	39 39	19.1 19.1	19.1		34.2 34.2	34.2	8.4 8.4	8.4	99.6 99.3	99.5	7.5 7.5	7.5	7.5	2.3	2.2		<0.001	<0.001		4.3	4.2		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
						S	0.57 0.57	299 299	19.5 19.5	19.5		34.5 34.5	34.5	8.3 8.3	8.3	99.1 98.4	98.8	7.4	7.4	7.4	1.1	1.2		<0.001	<0.001		2.5	2.7		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	F3	Cloudy	Moderate	9:54	18.0	М	0.7	293 293	19.5 19.5	19.5	19.5	34.5 34.5	34.5	8.3 8.3	8.3	99.1 99.2	99.2	7.4	7.4	7.54	1.2	1.2	1.3	<0.001	<0.001	<0.001	3.6	3.5	3.4	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
Mid						В	0.29 0.53	310 321	19.5 19.5	19.5		34.5 34.5	34.5	8.3 8.3	8.3	99.4 99.5	99.5	7.4 7.4	7.4	7.4	1.5	1.5		<0.001	<0.001		3.8 4.1	4.0		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
Floo	1					S	0.25 0.25	30 30	19.8 19.7	19.7		34.5 34.5	34.5	8.3 8.3	8.3	98.4 97.9	98.2	7.3 7.3	7.3	7.3	1.7	1.7		<0.001	<0.001		4.2 3.8	4.0		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	IM6	Cloudy	Moderate	9:38	17	М	0.34 0.18	16 56	19.7 19.7	19.7	19.7	34.5 34.5	34.5	8.3 8.3	8.3	98.8 98.8	98.8	7.4 7.4	7.4	7.3	2.3	2.4	2.9	<0.001	<0.001	<0.001	4.8 5.1	5.0	5.4	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
						В	0.21	19 292	19.7 19.7	19.7		34.5 34.5	34.5	8.3 8.3	8.3	99.5 99.1	99.3	7.4 7.4	7.4	7.4	4.3 5.0	4.7		<0.001	<0.001		7.1 7.5	7.3		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/02/08

Tic	. Monitor	ing Weather	Sea	Sampling	Water Depth	Depth	Current	Current	T	mperature (°	C)	Salinity (ppt)	pl	4	DO Satu	ration (%)	Disso	lved Oxygen (mg/L)	1	urbidity(NTU)	Total Res	idual Chlorin	e (mg/L)	Susper	nded Solids ((mg/L)	Total Inore	anic Nitrog	en (mg/L)	5-day Biochen	nical Oxygen De	mand (mg/L)
110	Statio	n Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.09	273 273	19.4 19.3	19.3		34.3 34.3	34.3	8.2 8.2	8.2	94.2 94.1	94.2	7.1 7.1	7.1	7.1	3.4	3.6		<0.001	<0.001		5.2 5.4	5.3		0.12 0.13	0.13		<1.0 <1.0	<1.0	
	E2	Cloudy	Moderate	11:12	9.3	М	0.19 0.19	104 104	19.4 19.4	19.4	19.3	34.3 34.3	34.3	8.2 8.2	8.2	94.8 94.5	94.7	7.1 7.1	7.1	7.1	3.1	3.3	3.3	<0.001 0.003	0.002	0.001	5.2 4.4	4.8	5.2	0.12 0.11	0.12	0.12	<1.0 <1.0	<1.0	<1.0
Mid-E						В	0.12 0.05	11 332	19.3 19.3	19.3		34.2 34.3	34.2	8.2 8.2	8.2	98.3 96.3	97.3	7.4 7.2	7.3	7.3	3.0	3.0		<0.001	<0.001		5.1 5.9	5.5		0.11 0.12	0.12		<1.0 <1.0	<1.0	
Wild-6	00					S	0.07 0.13	287 232	18.2 18.2	18.2		34.2 34.1	34.1	8.3 8.3	8.3	100.0	100.0	7.7 7.7	7.7	77	1.3	1.2		<0.001 <0.001	<0.001		2.2	2.5		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	IM6	Cloudy	Moderate	10:40	17.1	М	0.18 0.18	133 133	18.2 18.2	18.2	18.2	34.2 34.2	34.3	8.3 8.3	8.3	99.8 99.7	99.8	7.7	7.7	7.7	2.8	2.5	1.8	<0.001	<0.001	<0.001	4.5 6.4	5.5	3.9	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
						В	0.09	347 270	18.2 18.2	18.2		34.2 34.2	34.2	8.3 8.3	8.3	99.9 99.8	99.9	7.7	7.7	7.7	1.6	1.7		<0.001	<0.001		4.2 3.3	3.8		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
						S	0.28 0.16	312 314	18.3 18.3	18.3		34.1 34.1	34.1	8.4 8.4	8.4	107.6 107.6	107.6	8.3 8.3	8.3	8.3	0.7	0.7		<0.001 <0.001	<0.001		1.6 2.7	2.2		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	F3	Cloudy	Moderate	15:35	18.0	М	0.22 0.53	65 279	18.3 18.3	18.3	18.3	34.1 34.1	34.1	8.4 8.4	8.4	107.5 107.4	107.5	8.3 8.2	8.3	0.0	0.9	0.9	0.9	<0.001	<0.001	<0.001	1.6	1.6	1.8	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
Mic						В	0.65	318 327	18.3 18.3	18.3		34.1 34.1	34.1	8.4 8.4	8.4	107.8 107.6	107.7	8.3 8.3	8.3	8.3	1.0	1.2		<0.001	<0.001		1.4	1.6		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
Flo	od					s	0.26 0.31	307 332	18.1 18.1	18.1		34.1 34.1	34.1	8.3 8.4	8.4	106.5 106.8	106.7	8.2 8.2	8.2	8.2	1.0	1.0		<0.001 0.004	0.003		2.8	2.5		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	IM6	Cloudy	Moderate	15:22	17.3	М	0.16 0.16	313 313	18.1 18.2	18.1	18.1	34.1 34.1	34.1	8.3 8.3	8.3	106.1 106.3	106.2	8.2 8.2	8.2	U.Z	1.2	1.3	1.2	<0.001 <0.001	<0.001	0.002	2.4 2.6	2.5	2.7	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
						В	0.08	24	18.2 18.2	18.2		34.0 34.1	34.1	8.2 8.3	8.3	105.9 105.7	105.8	8.1 8.1	8.1	8.1	1.3	1.3		<0.001	<0.001		2.5	3.1		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/02/15

Tide	Monitoring	Weather	Sea	Sampling	Water Depth		Current	Current	Te	mperature (°	C)	Salini	ty (ppt)	F	Н	DO Satu	ration (%)	Dissol	lved Oxygen	mg/L)	T	urbidity(NTU)	Total Res	idual Chlorir	ne (mg/L)	Susper	nded Solids	(mg/L)	Total Inor	ganic Nitrog	en (mg/L)	5-day Biocher	nical Oxygen De	emand (mg/L)
Hue	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.12	63	19.5	197		34.0	33.9	8.3	8.3	108.8	109.2	8.2	8.2		1.7	17		<0.001	<0.001		3.3	3.2		0.11	0.11		<1.0	<1.0	
							0.19	142	20.0			33.9		8.3		109.6		8.2	5.12	8.1	1.7			<0.001			3.0	***		0.11	****		<1.0]
	E2	Fine	Calm	16:11	9.0	М	0.22	123	19.2	19.2	19.3	33.9	33.9	8.3	8.3	106.1	106.7	8.0	8.1		1.7	1.7	1.8	<0.001	<0.001	< 0.001	2.8	2.7	2.7	0.12	0.11	0.12	<1.0	<1.0	<1.0
							0.17	351	19.2			33.9		8.3		107.3		8.1			1.7			<0.001			2.6			0.10			<1.0		
						В	0.17	53	19.1	19.1		33.9	33.9	8.2	8.2	102.6	103.4	7.8	7.8	7.8	1.9	2.0		<0.001	<0.001		2.4	2.3		0.12	0.13		<1.0	<1.0	
Mid-Eb	-					_	0.17	121	19.1			33.9		8.2 8.3		104.1		7.9			2.1			<0.001			2.2 3.8			0.13			<1.0 <1.0		
						s	0.12	162	20.2	20.3		33.9	33.9	8.3	8.3	113.2	113.5	8.4	8.4		0.8	0.8		<0.001	<0.001		3.4	3.6		0.04	0.04		<1.0	<1.0	
						-	0.14	38	19.5			34.2		8.3		108.0		9.1		8.3	0.8			<0.001			3.1		1	<0.02		1	<1.0		1 1
	IM6	Fine	Calm	15:41	17.0	M	0.10	1	19.5	19.5	19.7	34.2	34.2	8.3	8.3	109.1	108.6	8.2	8.1		0.8	0.8	1.0	0.002	0.002	0.001	2.9	3.0	3.1	<0.02	<0.02	0.03	<1.0	<1.0	<1.0
						_	0.22	359	19.4	19.4		34.2	34.2	8.2		105.9		8.0		7.9	1.4			<0.001	<0.001		2.7		i	0.02			<1.0	<1.0	i l
						Ь в	0.22	359	19.4	19.4		34.2	34.2	8.2	8.2	105.1	105.5	7.9	7.9	7.9	1.3	1.4		< 0.001	<0.001		2.5	2.6		0.02	0.02		<1.0	<1.0	
						-	0.29	193	19.3	19.3		34.0	34.0	8.3	6.3	104.5	105.0	7.9	7.0		1.0	1.3		<0.001	<0.001		1.4	1.3		0.05	0.05		<1.0	<1.0	
						_ 。	0.17	284	19.3	19.3		34.0	34.0	8.3	0.3	105.4	100.0	7.9	7.9	7.8	1.1	1.3		<0.001	<0.001		1.2	1.3		0.05	0.05		<1.0	<1.0]
	F3	Cloudy	Calm	9:41	18.0	M	0.36	277	19.4	19.4	19.3	34.1	34.1	8.3	8.3	102.7	102.9	7.7	7.7	7.0	0.9	0.8	1.1	<0.001	<0.001	< 0.001	1.9	1.8	19	0.03	0.03	0.04	<1.0	<1.0	<1.0
		Oloudy	- Cuiiii	0.41	10.0		0.36	277	19.4	10.4	10.0	34.1	04.1	8.3	0.0	103.0	102.0	7.8	1		0.7	0.0		<0.001	-0.001	-0.001	1.6	1.0		0.03	0.00		<1.0	-1.0]
						В	0.18	62	19.3	19.3		34.1	34.1	8.3	8.3	102.1	102.1	7.7	7.7	7.7	1.4	1.4		<0.001	<0.001		2.3	2.5		0.04	0.04		<1.0	<1.0	
Mid-							0.18	62	19.3	- ' '		34.1		8.3	- ' '	102.1		7.7			1.4			<0.001			2.7			0.04			<1.0		
Flood						S	0.23	328	19.3	19.3		34.0	34.0	8.2	8.2	104.4	104.3	7.9	7.9		1.2	1.3		<0.001	0.004		3.1	2.9		0.04	0.05		<1.0	<1.0	
						_	0.05	355	19.3 19.3			34.0		8.2		104.2		7.9		7.9	1.3			0.007			2.7		ļ	0.05		-	<1.0		
	IM6	Cloudy	Calm	9:22	17.0	M	0.13	355	19.3	19.3	19.3	34.0	34.0	8.2 8.2	8.2	104.1	104.2	7.8	7.9		1.3	1.4	1.6	<0.001	<0.001	0.003	2.2	2.4	2.3	0.03	0.05	0.05	<1.0 <1.0	<1.0	<1.0
				1	1		0.33	300	19.3			34.0		8.2		104.3		7.9			1.4			<0.001			1.8		1	0.04			<1.0		1
						В	0.16	271	19.4	19.4		34.1	34.0	8.2	8.2	104.7	104.8	7.9	7.9	7.9	2.3	2.1		0.006	0.004		1.6	1.7		0.06	0.06		<1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/02/23

Tie	to 1	Monitoring	Weather	Sea	Sampling	Water Depth		Current	Current	Te	mperature (°	°C)	Salinity	(ppt)	р	Н	DO Satu	ration (%)	Dissol	lved Oxygen	(mg/L)	Т	urbidity(NTU)	Total Res	sidual Chlorin	ne (mg/L)	Susper	nded Solids	(mg/L)	Total Inorga	nic Nitroge	en (mg/L)	5-day Biocher	nical Oxygen De	mand (mg/L)
1 "		Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
							S	0.30 0.19	335 4	20.9	20.9		33.2 33.2	33.2	8.2 8.2	8.2	100.0 100.1	100.1	7.4	7.4	7.3	1.0	1.0		<0.001	<0.001		1.3	1.4		0.19	0.19		1.1	1.1	
		E2	Cloudy	Rough	12:02	9.0	М	0.19 0.22	164 317	20.8	20.8	20.8	33.1 33.1	33.1	8.2 8.2	8.2	99.6 99.7	99.7	7.3 7.3	7.3	7.5	1.4	1.4	1.3	<0.001 <0.001	<0.001	<0.001	1.6	1.7	1.8	0.20	0.20	0.20	<1.0 <1.0	<1.0	1.0
Mid-	Ebb						В	0.26 0.20	288 323	20.8	20.8		33.1 33.1	33.1	8.2 8.2	8.2	100.7 99.8	100.3	7.4	7.4	7.4	1.5	1.5		<0.001	<0.001		2.5	2.4		0.20	0.20		<1.0 <1.0	<1.0	
I WILLIAM							S	0.05 0.05	165 165	20.5 20.5	20.5		33.2 33.3	33.3	8.2 8.2	8.2	99.7 99.5	99.6	7.4	7.4	7.4	1.2	1.2		<0.001 0.003	0.002		2.9	2.8		0.28	0.27		4.4 3.6	4.0	
		IM6	Cloudy	Rough	11:25	17.0	М	0.10 0.06	19 274	20.5 20.5	20.5	20.5	33.3 33.3	33.3	8.2 8.2	8.2	99.5 99.4	99.5	7.4	7.4	7.4	0.8	0.8	1.1	<0.001 0.006	0.004	0.002	2.6	2.5	2.5	0.17	0.18	0.21	1.7	1.6	2.2
							В	0.11 0.11	312 312	20.5 20.5	20.5		33.3 33.3	33.3	8.2 8.2	8.2	99.8 99.6	99.7	7.4	7.4	7.4	1.3	1.4		<0.001	<0.001		2.1	2.2		0.18	0.18		1.2	1.2	
							S	0.57 0.34	289 260	20.7	20.7		33.5 33.5	33.5	8.2 8.2	8.2	103.6 102.9	103.3	7.6 7.6	7.6	7.6	0.1 0.1	0.1		<0.001 <0.001	<0.001		<1.0 <1.0	<1.0		0.23	0.25		<1.0 <1.0	<1.0	
		F3	Cloudy	Rough	6:20	17.0	М	0.41 0.41	235 235	20.7	20.7	20.6	33.7 33.6	33.7	8.3 8.2	8.2	104.2 104.1	104.2	7.7	7.7	7.0	0.1	0.1	0.4	<0.001	<0.001	0.001	1.5	1.4	1.4	0.16	0.16	0.14	<1.0 <1.0	<1.0	<1.0
Mi	d-						В	0.25 0.25	310 310	20.3	20.3		34.1 34.1	34.1	8.3 8.3	8.3	103.9 104.1	104.0	7.7	7.7	7.7	1.0 0.9	1.0		<0.001 0.002	0.002		1.9	1.8		0.02	0.02		<1.0 <1.0	<1.0	
Flo	od						S	0.32 0.37	307 235	20.7 20.7	20.7		33.2 33.2	33.2	8.2 8.2	8.2	104.3 104.3	104.3	7.7	7.7	7.7	0.0	0.0		<0.001 0.004	0.003		1.3 1.5	1.4		0.19 0.18	0.19		<1.0 <1.0	<1.0	
		IM6	Cloudy	Rough	6:02	16.0	М	0.28 0.11	229 270	20.6 20.6	20.6	20.6	33.6 33.6	33.6	8.3 8.3	8.3	105.0 104.9	105.0	7.7	7.7		1.0	1.0	1.3	<0.001	<0.001	0.003	2.3	2.5	2.5	0.13 0.12	0.13	0.13	<1.0 <1.0	<1.0	<1.0
							В	0.17	348 6	20.5	20.5		33.8 33.8	33.8	8.3 8.3	8.3	104.9 104.8	104.9	7.7	7.7	7.7	2.9	2.9		<0.001 0.007	0.004		3.6	3.8		0.08	0.08		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/02/28

Tide	Monitoring	Weather	Sea	Sampling	Water Depth		Current	Current	Te	mperature (°	C)	Salinit	y (ppt)	р	Н	DO Satu	ration (%)	Dissol	ved Oxygen	mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	e (mg/L)	Susper	nded Solids	(mg/L)	Total Inor	ganic Nitrog	en (mg/L)	5-day Biocher	nical Oxygen De	emand (mg/L)
Tid	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						S	0.10 0.14	282 107	19.9 19.9	19.9		33.9 33.9	33.9	8.2 8.2	8.2	101.8	101.9	7.6	7.6		2.4	2.4		<0.001	<0.001		1.8	2.3		0.08	0.08		1.1	1.1	
	E2	Cloudy	Rough	14:07	9.0	М	0.30	95	19.9	19.9	19.9	33.9	33.9	8.2	8.2	101.4	101.5	7.6	7.6	7.6	2.8	2.8	3.4	<0.001	<0.001	<0.001	1.9	2.0	2.2	0.08	0.08	0.08	<1.0	<1.0	1.0
						В	0.30 0.17	95 5	19.9 19.9	19.9		33.9 33.9 33.9	33.9	8.2 8.2 8.2	8.2	101.6	101.7	7.6 7.6	7.6	7.6	5.0	4.9		<0.001	<0.001		2.0 2.1 2.8	2.5		0.08 0.08 0.09	0.09		<1.0 <1.0 <1.0	<1.0	
Mid-E	bb					s	0.18 0.21 0.21	64 64	20.3	20.3		34.2 34.2	34.2	8.2 8.2	8.2	101.5 100.4 100.5	100.5	7.4	7.4		1.3	1.3		<0.001 <0.001 <0.001	<0.001		1.4	1.3		0.03	0.03		<1.0 <1.0 <1.0	<1.0	
	IM6	Cloudy	Rough	13:34	17.0	М	0.18 0.07	190	20.4	20.4	20.4	34.2	34.2	8.2 8.2	8.2	100.4	100.4	7.4	7.4	7.4	1.3	1.3	1.3	<0.001	<0.001	0.003	1.7	1.9	1.4	0.04	0.04	0.04	<1.0 <1.0	<1.0	<1.0
						В	0.28 0.04	48 269	20.4 20.4	20.2		34.3 34.3	34.3	8.2 8.2	8.2	101.1 100.6	100.9	7.5 7.4	7.4	7.4	1.3 1.3	1.3		<0.001	0.006		<1.0 <1.0	<1.0		0.04	0.04		<1.0 <1.0	<1.0	
						s	0.12 0.19	307 251	20.7	20.6		34.4 34.4	34.4	8.3 8.3	8.3	100.5 100.5	100.5	7.4	7.4	7.4	1.6 1.5	1.6		<0.001	0.001		<1.0 <1.0	<1.0		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	F3	Cloudy	Rough	8:04	18.0	М	0.49	283 275	20.6	20.6	20.6	34.4 34.4	34.4	8.3 8.3	8.3	100.3	100.3	7.4	7.4	/	1.3	1.3	1.8	<0.001	<0.001	0.144	<1.0 <1.0	<1.0	<1.0	<0.02 <0.02	<0.02	<0.02	<1.0 <1.0	<1.0	<1.0
Mid						В	0.54 0.41	309 301	20.6 20.6	20.6		34.4 34.4	34.4	8.3 8.3	8.3	101.5 101.0	101.3	7.5 7.4	7.4	7.4	2.6	2.5		<0.001	<0.001		<1.0 <1.0	<1.0		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
Floo	d					S	0.31 0.22	254 19	20.6 20.6	20.6		34.4 34.4	34.4	8.2 8.2	8.2	100.4 100.4	100.4	7.4	7.4	7.4	2.0	1.9		<0.001	<0.001		1.1	1.3		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	
	IM6	Cloudy	Rough	7:36	17.0	М	0.22	276 335	20.6 20.6	20.6	20.6	34.4 34.4	34.4	8.2 8.2	8.2	100.7 100.5	100.6	7.4 7.4	7.4	7.4	1.7	1.7	2.0	<0.001 <0.001	<0.001	<0.001	2.0	1.6	2.0	<0.02 0.03	0.03	0.02	<1.0 <1.0	<1.0	<1.0
						В	0.11 0.11	352 352	20.6 20.6	20.6		34.4 34.4	34.4	8.2 8.2	8.2	101.5 100.9	101.2	7.4	7.4	7.4	2.5 2.3	2.4		<0.001 <0.001	<0.001		3.6 2.4	3.0		<0.02 <0.02	<0.02		<1.0 <1.0	<1.0	

Remark: * DA: Depth-Averaged

** Calm: Small or no wave, Moderate: Between calm and rough; Rough: White capped or rougher

*** S: 1 m below the sea surface; M: mid-depth; B: 1 m above the seabed

Date: 2024/03/07

Tide	Monitoring	Weather	Sea	Sampling	Water Depth		Current	Current	Te	mperature (°	C)	Salini	y (ppt)	F	Н	DO Satu	ration (%)	Dissol	ved Oxygen (mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	ne (mg/L)	Susper	nded Solids	(mg/L)	Total Inor	ganic Nitrog	en (mg/L)	5-day Biocher	nical Oxygen De	emand (mg/L)
Tide	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.25	288	20.1	20.1		34.2	34.2	8.3	8.3	102.6	102.6	7.6	76		1.7	1.7		<0.001	<0.001		1.2	13		0.08	0.08		<1.0	<1.0	
							0.05	258	20.1			34.2		8.3		102.6		7.6		7.6	1.7			<0.001			1.3		!	0.08		1	<1.0		
	E2	Cloudy	Moderate	9:48	9.0	М	0.37	324	20.1	20.1	20.1	34.2	34.2	8.3	8.3	102.7	102.7	7.6	7.6		2.4	2.3	2.3	<0.001	<0.001	< 0.001	1.8	1.7	1.8	0.08	0.08	0.07	<1.0	<1.0	<1.0
		' '					0.13	160	20.1			34.2		8.3		102.7		7.6			2.2			<0.001			1.6			0.08			<1.0		
						В	0.18	205	20.1	20.1		34.2	34.2	8.3	8.3	103.1	103.0	7.7	7.6	7.6	3.0	3.0		<0.001	<0.001		2.5	2.6		0.01	0.05		<1.0	<1.0	
Mid-E	ь					_	0.25	245	20.1			34.2		8.3		102.9		7.6			2.9	- ' '		<0.001			2.6			0.08			<1.0		
						s	0.22	249	20.6	20.6		34.4	34.4	8.3	8.3	101.1	101.1	7.4	7.4		1.4	1.4		<0.001	< 0.001		<1.0	<1.0		0.05	0.06		<1.0	<1.0	
							0.25	245	20.6			34.4		8.3		101.0		7.4		7.4	1.3			<0.001			<1.0		ļ	0.07		1	<1.0		
	IM6	Cloudy	Moderate	9:16	17.0	M	0.30	269	20.6	20.6	20.6	34.4	34.4	8.3	8.3	101.1	101.1	7.4	7.4		1.8	1.8	2.0	<0.001	<0.001	< 0.001	1.6	1.7	1.7	0.06	0.06	0.06	<1.0 <1.0	<1.0	<1.0
							0.30	269 355	20.6			34.4		8.3		101.1		7.4			3.0			<0.001					-	0.06		1	<1.0		
						В	0.26	284	20.6	20.6		34.4	34.4	8.3	8.3	101.4	101.8	7.0	7.5	7.5	2.8	2.9		<0.001	<0.001		2.6	2.5		0.06	0.06		<1.0	<1.0	
	_					_	0.31	237	20.6			34.4		8.3		103.5		7.9			1.3			<0.001			<1.0			0.07			<1.0		
						S	0.31	328	20.6	20.6		34.4	34.4	8.3	8.3	104.0	103.8	7.6	7.6		1.2	1.3		<0.001	<0.001		<1.0	<1.0		0.07	0.07		<1.0	<1.0	
							0.28	242	20.6			34.4		8.3		102.4		7.5		7.6	1.3			<0.001			1.2			0.06		1	<1.0		
	F3	Cloudy	Moderate	14:24	17.0	M	0.04	41	20.6	20.6	20.6	34.4	34.4	8.3	8.3	102.9	102.7	7.6	7.5		1.2	1.3	4.1	<0.001	<0.001	<0.001	1.5	1.4	5.0	0.07	0.07	0.07	<1.0	<1.0	<1.0
							0.26	309	20.6	20.6		34.4	34.4	8.3	8.3	102.6	102.3	7.5	7.5	7.5	10.0	9.7		<0.001	<0.001		12.8	40.0	İ	0.06	0.07	1	<1.0	<1.0	i
Mid-						B	0.21	306	20.6	20.6		34.4	34.4	8.3	8.3	102.0	102.3	7.5	7.5	7.5	9.4	9.7		< 0.001	<0.001		12.3	12.6		0.07	0.07		<1.0	<1.0	
Floo						9	0.27	314	20.7	20.7		34.4	34.4	8.3	9.2	102.6	102.9	7.5	7.5		2.1	2.0		<0.001	<0.001		1.9	1.9		0.06	0.06		<1.0	<1.0	
						_ ,	0.24	244	20.8	20.7		34.4	34.4	8.3	0.5	103.0	102.0	7.5	7.5	7.5	1.9	2.0		<0.001	NO.001		1.8	1.0		0.06	0.00		<1.0	1.0	
	IM6	Cloudy	Moderate	14:10	16.0	M	0.06	241	20.7	20.7	20.7	34.4	34.4	8.3	8.3	101.7	101 7	7.5	7.5	7.5	3.1	3.0	2.5	<0.001	<0.001	< 0.001	1.8	1.7	17	0.07	0.07	0.07	<1.0	<1.0	<1.0
		Joseph	······································	1	.5.0		0.22	318	20.7	20.7	20.7	34.4	54.4	8.3	3.3	101.7	.01.7	7.5	7.5		2.9	0.0	2.0	< 0.001	-0.501	-0.001	1.6			0.07	5.01	1	<1.0	-1.0	0
	1				1	В	0.09	228	20.6	20.6		34.4	34.4	8.2	8.2	102.1	101.8	7.5	7.5	7.5	2.5	2.5		<0.001	<0.001		1.6	1.6		0.06	0.07		<1.0	<1.0	
							0.09	228	20.6			34.4	•	8.2		101.5		7.5			2.4			<0.001			1.6			0.07	5.5.		<1.0		

Date: 2024/03/14

Tic	. Monitor	ing Weather	Sea	Sampling	Water Depth	Depth	Current	Current	T	emperature (°	C)	Salinity (ppt)	pl	1	DO Satu	ration (%)	Dissol	ved Oxygen (mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	ne (mg/L)	Susper	nded Solids ((mg/L)	Total Inorg	anic Nitrog	en (mg/L)	5-day Biochen	nical Oxygen De	mand (mg/L)
110	Statio	n Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.27	45 66	19.8 19.8	19.8		34.0 34.0	34.0	8.2 8.2	8.2	104.2 104.5	104.4	7.8 7.8	7.8	7.7	2.1	2.1		<0.001	<0.001		1.7	1.8		0.13 0.14	0.14		<1.0 <1.0	<1.0	
	E2	Cloudy	Rough	14:47	9.0	М	0.19 0.14	319 65	19.7 19.7	19.7	19.7	34.1 34.1	34.1	8.2 8.2	8.2	102.3 102.6	102.5	7.7 7.7	7.7	1.1	2.3	2.3	2.7	<0.001	<0.001	<0.001	2.6 2.2	2.4	2.5	0.13 0.13	0.13	0.13	<1.0 <1.0	<1.0	<1.0
Mid-E						В	0.39 0.26	82 60	19.5 19.5	19.5		34.1 34.1	34.1	8.2 8.2	8.2	101.1 100.9	101.0	7.6 7.6	7.6	7.6	3.6 3.7	3.7		<0.001 <0.001	<0.001		3.3 3.0	3.2		0.11 0.12	0.12		<1.0 <1.0	<1.0	
Wild-6	-00					s	0.18 0.27	101 343	19.5 19.6	19.5		34.1 34.1	34.1	8.2 8.2	8.2	99.8 100.0	99.9	7.5 7.5	7.5	7.5	2.2	2.2		<0.001 0.001	0.001		2.4	2.5		0.07	0.07		2.2	2.5	
	IM6	Cloudy	Rough	14:12	17.0	М	0.29	114 109	19.5 19.5	19.5	19.6	34.2 34.2	34.2	8.2 8.2	8.2	99.5 99.4	99.5	7.5 7.5	7.5	7.5	2.7 3.0	2.9	2.5	<0.001	<0.001	0.001	2.2	2.2	2.2	0.04	0.04	0.05	<1.0 <1.0	<1.0	1.5
						В	0.17 0.11	157 270	19.7 19.6	19.7		34.3 34.3	34.3	8.2 8.2	8.2	100.1 99.9	100.0	7.5 7.5	7.5	7.5	2.3 2.6	2.5		<0.001	<0.001		1.9	1.9		0.04	0.04		<1.0 <1.0	<1.0	
						S	0.81	268 268	19.4 19.4	19.4		34.2 34.2	34.2	8.3 8.3	8.3	99.5 99.7	99.6	7.5 7.5	7.5	7.5	2.3	2.4		<0.001	<0.001		1.9	1.8		0.11	0.11		1.7 2.1	1.9	
	F3	Cloudy	Rough	8:10	18.0	М	0.47	311 272	19.4 19.4	19.4	19.4	34.2 34.2	34.2	8.3 8.3	8.3	99.9 99.4	99.7	7.5 7.5	7.5	7.0	3.0	3.1	3.3	<0.001	<0.001	<0.001	2.1	2.2	2.3	0.11	0.12	0.11	<1.0 <1.0	<1.0	1.4
Mic						В	0.40	286 290	19.4 19.4	19.4		34.2 34.2	34.2	8.3 8.3	8.3	100.7 100.0	100.4	7.6 7.5	7.5	7.5	4.0 5.2	4.6		<0.001	<0.001		2.6	2.8		0.11	0.11		1.6	1.4	
Flo	od					s	0.27 0.27	283 283	19.4 19.4	19.4		34.3 34.3	34.3	8.3 8.3	8.3	99.7 99.7	99.7	7.5 7.5	7.5	7.5	3.4	3.4		<0.001	<0.001		3.1	3.2		0.08	0.09		1.1	1.2	
	IM6	Cloudy	Rough	7:50	16.8	М	0.03	268 108	19.4 19.4	19.4	19.4	34.3 34.3	34.3	8.3 8.3	8.3	100.1 99.8	100.0	7.5 7.5	7.5	7.5	3.8	3.9	4.0	<0.001 <0.001	<0.001	0.002	3.6 3.4	3.5	3.6	0.08	0.09	0.08	<1.0 <1.0	<1.0	1.7
						В	0.28	10 298	19.4 19.4	19.4		34.3 34.3	34.3	8.3 8.3	8.3	101.4	101.0	7.6 7.6	7.6	7.6	4.5 4.8	4.7		<0.001 0.007	0.004		4.4	4.2		0.08	0.08		2.8	2.9	

Date: 2024/03/21

Tide	Monitoring	Weather	Sea	Sampling	Water Depth		Current	Current	T	emperature (°	C)	Salinit	y (ppt)	р	Н	DO Satu	ration (%)	Dissol	ved Oxygen	mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	e (mg/L)	Susper	nded Solids	(mg/L)	Total Inor	ganic Nitrog	en (mg/L)	5-day Biocher	nical Oxygen De	emand (mg/L)
Tide	Station	Condition	Condition**	Time	(m)	Level ***	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
						s	0.07	305	20.4	20.4		33.7	33.7	8.2	8.2	115.1	115.1	8.5	8.5		1.0	1.1		<0.001	<0.001		2.4	2.3		0.16	0.16		<1.0	<1.0	
							0.18	176	20.4			33.7		8.2		115.0		8.5		8.5	1.1			<0.001			2.1		!	0.16			<1.0		
	E2	Fine	Calm	10:47	9.0	М	0.31	16	20.4	20.4	20.4	33.8	33.8	8.2	8.2	114.0	114.3	8.4	8.5		1.0	1.0	1.1	<0.001	<0.001	< 0.001	2.8	2.7	2.7	0.14	0.14	0.15	1.0	1.0	1.0
							0.31	16	20.4			33.8		8.2		114.6		8.5			1.0			<0.001			2.6			0.14			1.0		
						В	0.16	100	20.4	20.4		33.8	33.8	8.3 8.2	8.2	109.8	111.0	8.1	8.2	8.2	1.3	1.2		<0.001	<0.001		3.0	3.2		0.14	0.14		<1.0 <1.0	<1.0	
Mid-Et	b					_	0.07	352 271	20.4			34.2		8.2		112.2		7.0			1.1			<0.001			3.6			0.13			<1.0		
						S	0.30	293	20.7	20.7		34.3	34.3	8.2	8.2	102.9	102.8	7.5	7.5		3.2	3.5		<0.001	<0.001		3.2	3.4		0.07	0.08		<1.0	<1.0	
	10.00	F	0.1	40.40	47.0		0.21	221	20.7	20.7	00.7	34.3	04.4	8.2	0.0	102.7	400.7	7.5	7.5	7.5	3.4	0.5		<0.001	-0.004	-0.004	4.2	4.0	4.0	0.08	0.00	0.08	<1.0	-4.0	
	IM6	Fine	Calm	10:13	17.0	I M	0.05	330	20.7	20.7	20.7	34.3	34.4	8.2	8.2	102.7	102.7	7.5	7.5		3.6	3.5	3.6	< 0.001	<0.001	<0.001	3.8	4.0	4.0	0.08	0.08	0.08	<1.0	<1.0	<1.0
						R	0.08	268	20.7	20.7		34.2	34.2	8.2	8.2	103.6	103.6	7.6	7.6	7.6	4.0	3.9		<0.001	<0.001		4.7	4.6	1	0.09	0.09	1	<1.0	<1.0	
							0.16	233	20.7	20.7		34.2	04.2	8.2	0.2	103.5	100.0	7.6	1.0	7.0	3.8	0.0		<0.001	-0.001		4.4	4.0		0.08	0.00		<1.0	-1.0	
						s	0.02	254	21.0	21.0		34.4	34.4	8.2	8.2	103.0	103.1	7.5	7.5		2.1	2.3		<0.001	<0.001		3.9	3.7		0.06	0.06		<1.0	<1.0	
							0.36	275	21.0			34.4		8.2		103.1		7.5		7.5	2.4			<0.001			3.4		ļ	0.06			<1.0		
	F3	Fine	Calm	15:19	18.2	M	0.21	259	21.0	21.0	20.9	34.4	34.4	8.2	8.2	102.2	102.4	7.5	7.5		1.9	1.9	2.4	<0.001	<0.001	< 0.001	3.0	3.2	3.2	0.06	0.07	0.06	<1.0	<1.0	<1.0
							0.28	254 293	21.0			34.4		8.2 8.2		102.5		7.5			1.9			<0.001			3.3 2.9			0.07			<1.0 <1.0		
Mid-						В	0.08	293	20.8	20.8		34.4	34.4	8.2	8.2	101.6	101.5	7.4	7.4	7.4	3.0	3.1		<0.001	<0.001		2.9	2.8		0.06	0.06		<1.0	<1.0	
Floor						—	0.51	266	20.8			34.1		8.2		105.6		7.7			1.6			<0.001			2.3			0.00			<1.0		
						S	0.51	266	20.8	20.8		34.1	34.1	8.2	8.2	106.4	106.0	7.8	7.8	7.7	1.6	1.6		0.005	0.003		2.6	2.5		0.10	0.10		<1.0	<1.0	
	11.40	F	0.1	45.04	47.0	·	0.34	240	20.8	00.0	00.0	34.2	34.2	8.2		102.9	400.0	7.5	7.6	7.7	2.2	0.0	22	<0.001	0.004	0.000	3.0		2.9	0.09	0.00	0.09	<1.0	.4.0	
	IM6	Fine	Calm	15:04	17.0	IVI	0.27	288	20.8	20.8	20.8	34.2	34.2	8.2	8.2	103.4	103.2	7.6	7.6		2.3	2.3	2.2	0.001	0.001	0.002	2.8	2.9	2.9	0.09	0.09	0.09	<1.0	<1.0	<1.0
	1				1	B	0.29	29	20.7	20.7		34.3	34.3	8.2	8.2	103.6	103.4	7.6	7.6	7.6	2.6	2.7		<0.001	<0.001		3.2	3.4]	0.08	0.08	1	<1.0	<1.0	
							0.29	29	20.7	20.7		34.3	04,0	8.2	0.2	103.1	100.4	7.6	1.0	7.0	2.7			<0.001	-0.001		3.6	0.4		0.08	0.00		<1.0	-1.0	

Date: 2024/03/28

Г	ide Mor	nitoring	Weather	Sea	Sampling	Water Depth	Depth	Current	Current	T	emperature (°	C)	Salinity	(ppt)	pl	1	DO Satu	ration (%)	Dissol	ved Oxygen (mg/L)	Т	urbidity(NTU)	Total Res	idual Chlorin	ne (mg/L)	Susper	nded Solids ((mg/L)	Total Inor	ganic Nitroge	en (mg/L)	5-day Biocher	nical Oxygen De	mand (mg/L)
Ι'	SI SI	tation	Condition	Condition**	Time	(m)	Level **	Velocity (m/s)	Direction	Value	Average	DA	Value	Average	Value	Average	Value	Average	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*	Value	Average	DA*
							s	0.16 0.24	136 129	23.1	23.1		33.2	33.2	8.4 8.4	8.4	135.8 135.2	135.5	9.6 9.6	9.6		0.1	0.1		<0.001	<0.001		1.6	1.7		0.12 0.12	0.12		1.0	1.1	
							_	0.49	52	22.8	_		33.3		8.4		135.2		9.0	-	9.6	0.1			<0.001			2.2			0.12	_		<1.0		
		E2	Cloudy	Calm	13:37	9.1	M	0.49	32	22.8	22.8	22.8	33.3	33.3	8.4	9.4	135.3	135.2	9.6	9.6		0.3	0.3	0.6	<0.001	<0.001	<0.001	2.4	2.3	2.2	0.11	0.10	0.12	<1.0	<1.0	1.0
							В	0.11 0.22	130	22.5 22.4	22.5		33.3 33.4	33.3	8.4 8.4	8.4	120.7 128.9	124.8	8.6 9.2	89.0	8.9	1.4	1.3		<0.001	<0.001		2.6	2.7		0.11	0.10		<1.0 <1.0	<1.0	
Mic	I-Ebb						S	0.13	153	22.3 22.5	22.4		33.7 33.3	33.5	8.3 8.3	8.3	110.7	114.3	7.9	8.2	7.9	0.2	0.2		<0.001	<0.001		2.9 2.6	2.8		0.09	0.10		1.4	1.4	
		IM6	Cloudy	Calm	13:04	17.0	М	0.30 0.10	63 130	21.9 21.9	21.9	22.1	34.3 34.3	34.3	8.2 8.2	8.2	105.7 105.8	105.8	7.6 7.6	7.6	7.9	0.7 0.8	0.8	0.6	<0.001 <0.001	<0.001	0.002	2.5 2.5	2.5	2.5	0.07	0.10	0.08	<1.0 <1.0	<1.0	1.1
							В	0.77 0.78	2 85	21.9 21.9	21.9		34.3 34.3	34.3	8.2 8.2	8.2	105.5 105.6	105.6	7.6 7.6	7.6	7.6	1.0	1.0		<0.001	0.005		2.2	2.2		0.07	0.10		<1.0 <1.0	<1.0	
							s	0.42 0.47	274 292	22.0 22.0	22.0		33.7 33.6	33.6	8.4 8.4	8.4	112.0 117.4	114.7	8.1 8.5	8.3	7.9	0.2	0.2		<0.001 0.052	0.027		1.8	1.7		0.09	0.10		<1.0 <1.0	<1.0	
		F3	Cloudy	Calm	7:05	18.0	М	0.17 0.17	321 321	21.9 21.9	21.9	21.9	34.4 34.4	34.4	8.3 8.3	8.3	106.0 106.1	106.1	7.6 7.6	7.6	7.5	0.5	0.6	0.6	<0.001	0.008	0.012	2.5	2.4	2.3	0.08	0.08	0.09	<1.0 <1.0	<1.0	<1.0
N.	/lid-						В	0.47	296 319	21.9 21.9	21.9		34.4 34.4	34.4	8.3 8.3	8.3	106.4 106.0	106.2	7.6 7.6	7.6	7.6	1.0	1.1		<0.001	<0.001		2.8 3.1	3.0		0.08	0.08		<1.0 <1.0	<1.0	
FI	lood						S	0.32 0.32	278 278	22.0 22.0	22.0		33.4 33.4	33.4	8.4 8.4	8.4	122.7 124.6	123.7	8.8 9.0	8.9	8.7	0.2	0.2		<0.001	<0.001		1.5	1.4		0.13 0.13	0.13		<1.0 <1.0	<1.0	
		IM6	Cloudy	Calm	6:52	16.0	М	0.15 0.15	325 325	22.0 22.0	22.0	22.0	33.8 33.8	33.8	8.4 8.4	8.4	117.4 119.6	118.5	8.4 8.6	8.5	0.7	0.3	0.3	0.3	<0.001	<0.001	0.015	1.8	1.7	1.8	0.13 0.13	0.13	0.12	<1.0 <1.0	<1.0	1.1
							В	0.19 0.23	313 335	22.0 22.0	22.0		34.0 34.1	34.1	8.3 8.3	8.3	115.7 114.4	115.1	8.3 8.2	8.3	8.3	0.4	0.5		<0.001 0.087	0.044		2.0	2.2		0.09	0.10		1.3	1.3	



ANNEX D

GRAPHICAL PRESENTATION OF OPERATION PHASE WATER QUALITY MONITORING RESULTS




Figure 1: Levels of Dissolved Oxygen (Surface and Middle) during mid-ebb tide between January and March 2024




Figure 2: Levels of Dissolved Oxygen (Bottom) during mid-ebb tide between January and March 2024

Kong Limited FSKU Pre-con EM&A.KC\U/ Data\15 Opera






Figure 3: Levels of Temperature during mid-ebb tide between January and March 2024




Figure 4: Levels of Turbidity during mid-ebb tide between January and March 2024






Figure 5: Levels of Suspended Solids during mid-ebb tide between January and March 2024




Figure 6: Levels of Total Inorganic Nitrogen during mid-ebb tide between January and March 2024






Figure 7: Levels of 5-day Biochemical Oxygen Demand during mid-ebb tide between January and March 2024




Figure 8: Levels of Total Residual Chlorine during mid-ebb tide between January and March 2024

Source: \\HKHKGDC02\Data\Hong Kong\Projects\0505354 CLP Power Hong

Kong Limited FSRU Pre-con EM&A.RC\07 Data\15 Operation WQ

April 2024 Date:






Figure 9: Levels of Dissolved Oxygen (Surface and Middle) during mid-flood tide between January and March 2024




Figure 10: Levels of Dissolved Oxygen (Bottom) during mid-flood tide between January and March 2024

Source: \\HKHKGDC02\Data\Hong Kong\Projects\0505354 CLP Power Hong

Kong Limited FSRU Pre-con EM&A.RC\07 Data\15 Operation WQ






Figure 11: Levels of Temperature during mid-flood tide between January and March 2024




Figure 12: Levels of Turbidity during mid-flood tide between January and March 2024

Limited FSRU Pre-con EM&A.RC\07 Data\15 Operation WQ






Figure 13: Levels of Suspended Solids during mid-flood tide between January and March 2024




Figure 14: Levels of Total Inorganic Nitrogen during mid-flood tide between January and March 2024

Source: \\HKHKGDC02\Data\Hong Kong\Projects\0505354 CLP Power Hong

Kong Limited FSRU Pre-con EM&A.RC\07 Data\15 Operation WQ






Figure 15: Levels of 5-day Biochemical Oxygen Demand during mid-flood tide between January and March 2024




Figure 16: Levels of Total Residual Chlorine during mid-flood tide between January and March 2024

